

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/001577

International filing date: 26 April 2005 (26.04.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB  
Number: 0409291.2  
Filing date: 27 April 2004 (27.04.2004)

Date of receipt at the International Bureau: 07 July 2005 (07.07.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 10 June 2005



Patents Form 1/77

Patents Act 1977  
(Rule 16)

THE PATENT OFFICE

27 APR 2004

NEWPORT



27APR04 EP91505-1 C49103

P01/7700 0.00-0409291.2 MHE

1/77

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

## Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

PTD/bk/2731

2. Patent application number

0409291.2

27 APR 2004

(The Patent Office will fill in this part)

3. Full name, address and postcode of the or of each applicant (*underline all surnames*)

Smith & Nephew, plc  
15 Adam Street  
LONDON WC2N 6LA

Patents ADP number (*if you know it*)

03969284001

3969284006

If the applicant is a corporate body, give the country/state of its incorporation

4. Title of the invention

Apparatus with Stress

5. Name of your agent (*if you have one*)

"Address for service", in the United Kingdom to which all correspondence should be sent (*including the postcode*)

Peter Draggett  
Group Patents & Trade Marks  
Smith & Nephew plc  
Research Centre  
York, YO10 5DF  
United Kingdom

3969284004

Patents ADP number (*if you know it*)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number  
(*if you know it*)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

YES

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

67

Claim(s)

Abstract

Drawing(s)

6+6

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

P. A. Draggett

Date

26/4/04

Peter Draggett

12. Name and daytime telephone number of person to contact in the United Kingdom

Peter Draggett 01904 4051

**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

**Notes**

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

## APPARATUS WITH STRESS

The present invention relates to apparatus and a medical wound dressing for irrigating, stressing and/or cleansing wounds, and a method of treating  
5 wounds using such apparatus for irrigating, stressing and/or cleansing wounds.

It relates in particular to such an apparatus, wound dressing and method that can be easily applied to a wide variety of, but in particular chronic, wounds, to  
10 cleanse them of materials that are deleterious to wound healing, whilst retaining materials that are beneficial in some therapeutic aspect, in particular to wound healing.

Before the present invention, aspirating and/or irrigating wounds and  
15 apparatus therefor were known, and tended to be used to remove wound exudate during wound therapy. In known forms of such wound therapy, the offtake from the wound, especially when in a highly exuding state, is voided to waste, e.g. to a collection bag.

20 Materials deleterious to wound healing are removed in this way.

However, materials that are beneficial in promoting wound healing, such as growth factors, naturally occurring anti-inflammatories, and other physiologically active components of the exudate from a wound are lost to  
25 the site where they can be potentially of most benefit, i.e. the wound bed, when such therapy is applied.

It thus would be desirable to provide a system of therapy which

- a) can remove materials deleterious to wound healing from wound exudate,  
30 whilst retaining materials that are beneficial in promoting wound healing in contact with the wound bed, and/or
- b) which allows fluids containing active amounts of materials that are beneficial in promoting wound healing to pass into and/or through the wound in contact with the wound bed.

35

Dialysis is a known method of treating bodily fluids such as blood ex vivo, to cleanse them of materials that are deleterious to the body systemically.

Retaining materials that are beneficial in some therapeutic aspect in the treated fluid is not an object of dialysis.

5 This method of treating bodily fluids is also a systemic therapy, since the treated fluid is returned to within the body.

This is in contrast to a topical therapy in which the treated fluid is recycled outside the body, e.g. to a wound.

10 Dialysis also requires large amounts either of bodily fluids, such as blood; or of dialysate, and consequently the relevant devices tend not to be portable.

Even when in a highly exuding state, chronic wounds produce relatively little fluid to be treated and relatively little materials that are beneficial in some  
15 therapeutic aspect to be retained in the wound and/or its environment.

It is an object of the present invention

- a) to obviate at least some of the abovementioned disadvantages of known aspiration and/or irrigation therapy systems, and
- 20 b) to provide a system of therapy which
  - i) can remove materials deleterious to wound healing from wound exudate, whilst retaining materials that are beneficial in promoting wound healing in contact with the wound bed, and/or
  - 25 ii) which allows fluids containing active amounts of materials that are beneficial in promoting wound healing to pass into and/or through the wound in contact with the wound bed.

It is a further object of the present invention

- a) to obviate at least some of the abovementioned disadvantages of known  
30 dialysis systems, and
- b) to provide a system of therapy which
  - i) can remove materials deleterious to wound healing from wound exudate, whilst retaining materials that are beneficial in promoting wound healing in contact with the wound bed, and

- ii) further allows fluids containing active amounts of materials that are beneficial in promoting wound to pass into and/or through the wound in contact with the wound bed, without affecting the body systemically.

5

It is a yet further object of the present invention

- a) to obviate at least some of the abovementioned disadvantages of known dialysis systems, and
- b) to provide a system of therapy which
  - 10 i) can remove materials deleterious to wound healing from wound exudate, whilst retaining materials that are beneficial in promoting wound healing in contact with the wound bed, and
  - ii) further allows fluids containing active amounts of materials that are beneficial in promoting wound to pass into and/or through the wound in contact with the wound bed without affecting the body systemically, and
  - 15 iii) is portable.

20 Additionally, known forms of wound dressing and aspiration and/or irrigation therapy systems often create a wound environment under the backing layer that may result in the loss of optimum performance of the body's own tissue healing processes, and slow healing and/or in weak new tissue growth that does not have a strong three-dimensional structure adhering well to and growing from the wound bed. This is a significant disadvantage, in particular in chronic wounds.

25

It is an object of the present invention

- a) to obviate at least some of the abovementioned disadvantages of known wound dressing, and
  - 30 b) to provide a system of therapy which
    - i) can remove materials deleterious to wound healing from wound exudate, whilst retaining materials that are beneficial in promoting wound healing in contact with the wound bed, and
    - ii) which creates stress across the wound bed and optionally tissue surrounding the wound, e.g. by applying an optionally varying positive and/or negative pressure to the wound.
- 35



Such a stress across the wound bed and optionally tissue surrounding the wound, e.g. an optionally varying positive and/or negative pressure applied to the wound, has been found to result in an increase in improvements to wound healing, such as an increase in cell proliferation, revascularisation, improved breaking strength and reduction of wound recurrence. The resultant tissue growth has a strong three-dimensional structure adhering well to and growing from the wound bed. It also stimulates blood flow in underlying tissue and optionally tissue surrounding the wound.

Removal of fluid by optionally varying negative pressure leads to reduction of interstitial oedema and pressure directly affecting the lymphatic and capillary system, restoring lymph function.

All of these are beneficial to wound healing.

Thus, according to a first aspect of the present invention there is provided an apparatus for irrigating, stressing and/or cleansing wounds, characterised in that it comprises

- a) a fluid flow path, comprising
  - i) a conformable wound dressing, having
    - a backing layer which is capable of forming a relatively fluid-tight seal or closure over a wound and
    - at least one inlet pipe for connection to a fluid supply tube, which passes through and/or under the wound-facing face, and
    - and at least one outlet pipe for connection to a fluid offtake tube, which passes through and/or under the wound-facing face,
    - the point at which the or each inlet pipe and the or each outlet pipe passes through and/or under the wound-facing face forming a relatively fluid-tight seal or closure over the wound,
    - at least one inlet pipe being connected to a fluid recirculation tube, and
    - at least one outlet pipe being connected to a fluid offtake tube: and
  - ii) a means for fluid cleansing having at least one inlet port connected to a fluid offtake tube and at least one outlet port connected to a fluid recirculation tube;

- b) a fluid reservoir connected by a fluid supply tube to an integer of the flow path (optionally or as necessary via means for flow switching between supply and recirculation);
  - c) a device for moving fluid through the wound dressing and means for fluid cleansing, and optionally or as necessary the fluid supply tube;
  - d) means for stressing the wound bed and optionally tissue surrounding the wound; and
  - e) means for bleeding the flowpath,
- such that fluid may be supplied to fill the flowpath from the fluid reservoir via the fluid supply tube (optionally or as necessary via the means for flow switching) and recirculated by the device through the flow path.

As noted hereinbefore, the present invention in this aspect advantageously provides a means for combining more than one therapy in a single dressing system, such as

- a) removal of materials deleterious to wound healing from wound exudate, whilst retaining materials that are beneficial in promoting wound healing, and
- b) promoting wound healing, by stimulating new tissue growth adhering well to and growing from the wound bed, by creating stress across the wound bed and optionally tissue surrounding the wound.

It may aid in the debridement of slough, eschar and necrotic tissue growth from the wound;

In all relevant embodiments of the present apparatus for irrigating, stressing and/or cleansing wounds, it is advantageous that it additionally, where appropriate, comprises a system which can regulate the pressure on the wound bed, under the wound dressing.

Preferably such a system is a conventional automated, programmable system which can maintain the wound at or near an appropriate, desired stress to the wound bed and optionally tissue surrounding the wound, to an appropriate, desired programme while moving fluid over the wound bed and through the means for fluid cleansing at an appropriate, desired rate.

Examples of suitable means for the stimulation of the healing of wounds and tissue adhering well to and growing from the wound bed include applying mechanical stimulus to the wound bed and optionally tissue surrounding the wound via the wound dressing and/or via the fluid under dressing.

5

Examples of suitable ways in which this can in turn be achieved include applying an optionally varying positive and/or negative pressure at any appropriate point for stressing the wound.

- 10 The positive and/or negative pressure on the wound bed and optionally tissue surrounding the wound and/or the fluid thereover may be constant, but more usually is varied, preferably cyclically, either randomly or regularly.

- 15 The stimulation of the healing of wounds in the present invention may also be effected by agitation of the wound bed and/or creating intermittent flow and/or turbulence to stimulate the cells. This can be done preferably by regularly or randomly pulsing a positive and/or negative pressure applied to the wound at any appropriate point for this purpose.

- 20 Pulsing the pressure on the wound may advantageously also provide a means to over-ride pain, similar to TENS.

- 25 The range of variation of the pulsed positive and/or negative pressure applied to the wound will be substantially less than the maximum levels of pressure referred to below.

- 30 The frequencies of such pulsed stressing across the wound will be substantially higher than those of the cycles of positive and/or negative pressure to the wound bed and optionally tissue surrounding the wound for the stimulation of the healing of wounds referred to above, but substantially less than the frequencies of ultrasound used on the wound bed and optionally tissue surrounding the wound conventionally.

- 35 Stimulus to the wound bed and optionally tissue surrounding the wound by applying an optionally varying positive and/or negative pressure and agitation of the wound bed to stimulate the cells by regularly or randomly pulsing any

pressure applied to the wound are mutually compatible. They may, as appropriate, be applied alone or together.

5 Thus, an embodiment of the apparatus for irrigating, stressing and/or cleansing wounds of the present invention is characterised in that it comprises means for supplying optionally varying positive and/or negative pressure, which is optionally pulsed, to a wound bed and optionally tissue surrounding the wound for the stimulation of the healing of the wound.

10 As noted hereinbefore, in the present invention in this aspect, the positive and/or negative pressure on the wound bed and optionally tissue surrounding the wound and/or the fluid thereover may be constant, but more usually is varied, preferably cyclically, either randomly or regularly.

15 Examples of maximum levels of such pressure above and below atmospheric include 50% atm. e.g. between 15 and 35%.

Examples of suitable frequencies of such regular cycles of pressure for the stimulation of the healing of wounds include 1 to 48 per 24hr.

20 Examples of preferred frequencies of such regular cycles of pressure for the stimulation of the healing of wounds include 12 to 24 per 24hr, e.g. 2 to 1 per hr.

25 Examples of suitable waveforms of such cycles either regularly or randomly for the stimulation of the healing of wounds include curved, e.g. sinusoidal, and sawtooth for higher frequencies, and usually square for lower frequencies.

30 Examples of suitable frequencies of regular pulses for the stimulation of the healing of wounds include 1 to 60 per min, e.g. 5 to 10 per min.

Examples of preferred frequencies of regular pulses for the stimulation of the healing of wounds include 30 to 60 per min, e.g. 10 to 20 per min.

35

Examples of suitable waveforms of such pulses either regularly or randomly for the stimulation of the healing of wounds include curved, e.g. sinusoidal, sawtooth, square and a systolic-diastolic asymmetric sawtooth.

- 5 Examples of means for applying an optionally varying positive and/or negative pressure at any appropriate point for stressing the wound and/or regularly or randomly pulsing any pressure applied to the wound for promoting wound healing, whether applied alone or together, include a wound dressing as hereinbefore defined that comprises one or more  
10 expandable and contractible modules capable of applying pressure to the wound bed and optionally tissue surrounding the wound at any appropriate point for stressing the wound.

- 15 Examples of other suitable means of applying mechanical stimulus to the wound by optionally varying positive and/or negative pressure include a magnetic fluid in a chamber or other hollow structure under the backing layer of the dressing in contact with the wound bed and/or the fluid thereover to which a regularly or randomly (preferably cyclically) varying and/or pulsing external magnetic field is applied. However, such means are less favoured.

- 20 Thus, one favoured embodiment of the apparatus for irrigating, stressing and/or cleansing wounds is characterised in that it comprises a wound dressing as hereinbefore defined that comprises one or more expandable and contractible modules capable of applying pressure to the wound bed and  
25 optionally tissue surrounding the wound at any appropriate point for stressing the wound.

- 30 This means should be capable of maintaining the pressure on the wound bed and/or the fluid thereover and optionally tissue surrounding the wound at a constant level, but more usually it should also be capable of regularly or randomly (preferably cyclically) varying and/or pulsing the pressure applied to the wound, all at or near an appropriate, desired level of stress to the wound bed and optionally tissue surrounding the wound, to an appropriate, desired programme while moving fluid over the wound bed and through the means  
35 for fluid cleansing at an appropriate, desired rate.

Examples of suitable modules capable of applying pressure to the wound bed at any appropriate point for stressing the wound include a module in the wound dressing may be made of a polymer that can be electrically stimulated to change shape repeatedly as appropriate frequencies.

5

A preferred module is a fluid-inflatable body that lies in the wound in use.

10

Thus, one favoured embodiment of the apparatus for irrigating, stressing and/or cleansing wounds is characterised in that it comprises a wound dressing as hereinbefore defined that comprises one or more fluid-inflatable modules capable of applying pressure to the wound bed at any appropriate point for stressing the wound.

15

This is capable of maintaining the pressure on the wound bed and/or the fluid thereover at a constant level, but more usually it is also capable of regularly or randomly (preferably cyclically) varying and/or pulsing the pressure applied to the wound, all at or near an appropriate, desired level of stress to the wound bed, to an appropriate, desired programme while moving fluid over the wound bed

20

The module or modules is/are (usually cyclically) inflated and deflated by admitting and releasing fluid.

25

Once the inflatable body has been inflated, it may be deflated as appropriate or desired, and then reinflated to again apply a positive pressure to the wound, and the cycle may be repeated as appropriate or desired.

30

Alternatively, it may be partially filled with an elastically resilient material, such as an elastomeric foam, that in its rest state is capable of applying a working pressure to the wound bed. The body may then be deflated as appropriate or desired, and then reinflated under the action of its filler material to again apply a positive pressure to the wound, and the cycle may be repeated as appropriate or desired.

35

Examples of forms of the body that are suitable such expandable and contractible modules capable of applying pressure to the wound bed at any

appropriate point for stressing the wound include fluid-inflatable fillers and fluid-inflatable irrigant inlet manifolds comprised in the dressing as described hereinafter in greater detail.

- 5 Where the module is a fluid-inflatable filler, examples of suitable fluids include gases, such as air and nitrogen; liquids, such as water and saline; gas in liquid aerosols; and gels such as those described in greater detail hereinafter. Preferred fluids include gases, such as air or nitrogen.
- 10 Where the module is a fluid-inflatable irrigant inlet manifold comprised in the dressing as described hereinafter in greater detail, it will be stimulated to change shape as appropriate and optionally at desired frequencies by inflation with irrigant, followed as desired by deflation.
- 15 Examples of both are included hereinafter.

Examples of such fillers include a substantially flat film, sheet or membrane, defining a chamber, pouch or other structure of the backing layer, e.g. of polymer film, which can contain the fluid.

- 20 It is provided with an inflation device for moving inflation fluid to the filler, and is connected to it by an inflation tube which communicates with its internal space.

- 25 The inflation device may also serve as a deflation device for moving inflation fluid from the filler, and the inflation tube also serves as a deflation tube.

Alternatively or additionally, where appropriate the filler as hereinbefore defined may have a deflation pipe and a bleed valve to waste, e.g. to a collection bag if a non-gaseous fluid is used.

- 30 The inflation device for moving then only serves as an inflation device to apply a positive pressure on the wound bed.

Less usually, the filler may have an inflation pump and a deflation pump.

Where it lies under the backing layer of the wound dressing of the apparatus of the invention, the inflation tube may run to the filler within the wound under the wound-facing face of the wound dressing.

- 5     However, the inflation tube may be connected to an inflation pipe that passes through the wound-facing face of the backing layer, the point at which the inflation pipe passes through the wound-facing face forming a relatively fluid-tight seal.
- 10    The inflation pipe may be in the form of an aperture, such as a funnel hole, opening, orifice, luer, slot or port for connection as a female member respectively to a mating end of the inflation tube (optionally or as necessary via means for forming a tube, pipe or hose, or nozzle).
- 15    Where the pipe passes through, rather than under the backing layer, the backing layer may often have a rigid and/or resiliently inflexible or stiff area to resist any substantial play between the or each pipe and the or each mating tube, or deformation under pressure in any direction.
- 20    It may often be stiffened, reinforced or otherwise strengthened by a boss projecting distally (outwardly from the wound) around each relevant tube, pipe or hose, or nozzle, hole, opening, orifice, luer, slot or port for connection to a mating end of the inflation tube.
- 25    The components may be a push, snap or twist-lock fit with each other.

The minimum calibre of the inflation tube and pipe must be sufficient for them to permit as rapid inflation and deflation of the filler as is desired.

- 30    Suitably the range of cross-dimensions of the bore may be 0.5 to 6 mm, e.g. 1.5 to 2 mm.

- Each should be resiliently flexible, and preferably soft with good conformability. This can be done for example by forming it of a suitable material, e.g. a resilient thermoplastic.
- 35



Examples of suitable inflation device for moving fluid into the filler include pumps. As noted above, the inflation device may also serve as a deflation device for moving inflation fluid from the filler, and the inflation tube also serves as a deflation tube. In such case, the pump must be a reversible pump used to increase and decrease the pressure on the wound bed as desired.

Subject to this consideration, the type and/or capacity of the device will also be largely determined by the appropriate or desired positive or negative pressure to the wound bed, the nature of the fluid, i.e. whether it is a gas, such as air and nitrogen; a liquid, such as water and saline; a gas in liquid aerosol; or a gel; the desired frequencies and waveforms of such cycles either regularly or randomly.

The following types of pump may be used to apply positive pressure, as desired to the filler through an inflation tube which communicates with its internal space:

reciprocating pumps, such as:

- syringe or piston pumps - providing high pressure and high accuracy;
- diaphragm pumps - where pulsations of one or two flexible diaphragms displace liquid while check valves control the direction of the fluid flow e.g. preferably a small portable diaphragm pump.

and

rotary pumps, such as:

- centrifugal pumps - with rotating vaned disk attached to a drive shaft moving fluid without pulsation as it spins. The outlet can be restricted without damaging the pump.
- peristaltic pumps - with rollers on a rotor acting on fluid in a tube, e.g. preferably a small portable peristaltic pump.

Of these, only piston pumps and rotary pumps, such as centrifugal pumps and peristaltic pumps are readily reversible pumps that may be used to increase and decrease the pressure on the wound bed as desired.

- 5 Subject to this consideration, preferred reversible pumps include a small portable peristaltic pump.

Preferred non-reversible pumps to be used with a bleed valve to the filler then include a small portable syringe pump (which is often used once and then disposed of) or small portable diaphragm pump, e.g. a sphygmometric pump.

15 As noted hereinbefore, stimulation of the healing of wounds in the present invention may also be effected by regularly or randomly pulsing a pressure applied to the wound at any appropriate point for this purpose.

Such pulsed pressure on the wound may be provided by some types of the device for moving fluid into the filler.

20 Where the module is a fluid-inflatable irrigant inlet manifold comprised in the dressing as described herein after in greater detail, it will be stimulated to change shape as appropriate and optionally at desired frequencies by inflation with irrigant, followed as desired by partial deflation.

25 The device for moving fluid through the wound and means for fluid cleansing is used to move irrigant to inflate the inlet manifold and apply a positive pressure to the wound bed. As noted hereinafter, the device may suitably be a pump.

30 As noted hereinbefore, the pressure on the wound bed may be constant, but may be varied, preferably cyclically, either randomly or regularly.

To achieve this, the present apparatus, where appropriate, comprises a system that can regulate the pump output to the inlet manifold in the wound dressing.

Preferably such a system is a conventional automated, programmable system which can maintain the wound at or near an appropriate, desired flow stress to the wound bed to an appropriate, desired programme while moving fluid over the wound bed.

5

As noted hereinbefore, stimulation of the healing of wounds in the present invention may also be effected by regularly or randomly pulsing a pressure applied to the wound at any appropriate point for this purpose.

10 Such pulsed flow across the wound may be provided by some types of the device for moving fluid through the wound and means for fluid cleansing. Certain diaphragm pumps described hereinafter in greater detail will be appropriate for this purpose, as are certain peristaltic pumps, and an  
15 electromechanical oscillator directly coupled to the wound dressing, will be suitable.

Suitable materials for such modules of any type include synthetic polymeric materials that do not absorb aqueous fluids, such as polyolefins, polysiloxanes and polyesters. They may be hydrophilic, and thus also  
20 include hydrophilic polyurethanes. They also include thermoplastic elastomers and elastomer blends, for example copolymers, such as ethyl vinyl acetate polystyrene and elastomeric polyurethane formed by solution casting.

25 In all embodiments of the apparatus of this first aspect of the present invention for aspirating, irrigating and/or cleansing wounds, a particular advantage is the tendency of the wound dressing to conform to the shape of the bodily part to which it is applied.

30 The wound dressing comprises a backing layer with a wound-facing face which is capable of forming a relatively fluid-tight seal or closure over a wound and

at least one inlet pipe for connection to a fluid supply tube or recirculation tube, which passes through and/or under the wound-facing face, and

35 and at least one outlet pipe for connection to a fluid offtake tube, which passes through and/or under the wound-facing face,

the point at which the or each inlet pipe and the or each outlet pipe passes through and/or under the wound-facing face forming a relatively fluid-tight seal or closure.

- 5 The term 'relatively fluid-tight seal or closure' is used herein to indicate one which is fluid- and microbe-impermeable and permits a positive or negative pressure of up to 50% atm., more usually up to 15% atm. to be applied to the wound. The term 'fluid' is used herein to include gels, e.g. thick exudate, liquids, e.g. water, and gases, such as air, nitrogen, etc.

- 10 The shape of the backing layer that is applied may be any that is appropriate to aspirating, irrigating and/or cleansing the wound across the area of the wound.

- 15 Examples of such include a substantially flat film, sheet or membrane, or a bag, chamber, pouch or other structure of the backing layer, e.g. of polymer film, which can contain the fluid.

- 20 The backing layer may be a film, sheet or membrane, often with a (generally uniform) thickness of up to 100 micron, preferably up to 50 micron, more preferably up to 25 micron, and of 10 micron minimum thickness.

- 25 Its largest cross-dimension may be up to 500 mm (for example for large torso wounds), up to 100 mm (for example for axillary and inguinal wounds), and up to 200 mm for limb wounds (for example for chronic wounds, such as venous leg ulcers and diabetic foot ulcers).

- Desirably the dressing is resiliently deformable, since this may result in increased patient comfort, and lessen the risk of inflammation of a wound.

- 30 Suitable materials for it include synthetic polymeric materials that do not absorb aqueous fluids, such as polyolefins, such as polyethylene e.g. high-density polyethylene, polypropylene, copolymers thereof, for example with vinyl acetate and  
35 polyvinyl alcohol, and mixtures thereof; polysiloxanes;

polyesters, such as polycarbonates; polyamides, e.g. 6-6 and 6 - 10, and hydrophobic polyurethanes.

They may be hydrophilic, and thus also include hydrophilic polyurethanes.

5

They also include thermoplastic elastomers and elastomer blends, for example copolymers, such as ethyl vinyl acetate, optionally or as necessary blended with high-impact polystyrene.

- 10 They further include elastomeric polyurethane, particularly polyurethane formed by solution casting.

Preferred materials for the present wound dressing include thermoplastic elastomers and curable systems.

15

The backing layer is capable of forming a relatively fluid-tight seal or closure over the wound and/or around the inlet and outlet pipe(s).

20

However, in particular around the periphery of the wound dressing, outside the relatively fluid-tight seal, it is preferably of a material that has a high moisture vapour permeability, to prevent maceration of the skin around the wound.

25

It may also be a switchable material that has a higher moisture vapour permeability when in contact with liquids, e.g. water, blood or wound exudate. This may, e.g. be a material that is used in Smith & Nephew's Allevyn™, IV3000™ and OpSite™ dressings.

30

The periphery of the wound-facing face of the backing layer may bear an adhesive film, for example, to attach it to the skin around the wound. This may, e.g. be a pressure-sensitive adhesive, if that is sufficient to hold the wound dressing in place in a fluid-tight seal around the periphery of the wound-facing face of the wound dressing.

35

Alternatively or additionally, where appropriate a light switchable adhesive could be used to secure the dressing in place to prevent leakage.

(A light switchable adhesive is one the adhesion of which is reduced by photocuring. Its use can be beneficial in reducing the trauma of removal of the dressing.)

5 Thus, the backing layer may have a flange or lip extending around the proximal face of the backing layer, of a transparent or translucent material (for which it will be understood that materials that are listed above are amongst those that are suitable).

10 This bears a film of a light switchable adhesive to secure the dressing in place to prevent leakage on its proximal face, and a layer of opaque material on its distal face.

15 To remove the dressing and not cause excessive trauma in removal of the dressing, the layer of opaque material on the distal face of the flange or lip extending around the proximal wound is removed prior to application of radiation of an appropriate wavelength to the flange or lip.

20 If the periphery of the wound dressing, outside the relatively fluid-tight seal, that bears an adhesive film to attach it to the skin around the wound, is of a material that has a high moisture vapour permeability or is a switchable material, then the adhesive film, if continuous, should also have a high or switchable moisture vapour permeability, e.g. be an adhesive such as used in Smith & Nephew's Allevyn™, IV3000™ and OpSite™ dressings.

25 Where a vacuum, is applied to hold the wound dressing in place in a fluid-tight seal around the periphery of the wound-facing face of the wound dressing, the wound dressing may be provided with a silicone flange or lip to seal the dressing around the wound. This removes the need for adhesives  
30 and associated trauma to the patient's skin.

Where the interior of, and the flow of irrigant and/or wound exudate to and through, the dressing is under any significant positive pressure, which will tend to act at peripheral points to lift and remove the dressing off the skin  
35 around the wound.

In such use of the apparatus, it may thus be necessary to provide means for forming and maintaining such a seal or closure over the wound against such positive pressure on the wound, to act at peripheral points for this purpose.

- 5 Examples of such means include light switchable adhesives, as above, to secure the dressing in place to prevent leakage.

10 Since the adhesion of a light switchable adhesive is reduced by photocuring, thereby reducing the trauma of removal of the dressing, a film of a more aggressive adhesive may be used, e.g. on a flange, as above.

15 Examples of suitable fluid adhesives for use in more extreme conditions where trauma to the patient's skin is tolerable include ones that consist essentially of cyanoacrylate and like tissue adhesives, applied around the edges of the wound and/or the proximal face of the backing layer of the wound dressing, e.g. on a flange or lip.

20 Further suitable examples of such means include adhesive (e.g. with pressure-sensitive adhesive) and non-adhesive, and elastic and non-elastic straps, bands, loops, strips, ties, bandages, e.g. compression bandages, sheets, covers, sleeves, jackets, sheathes, wraps, stockings and hose, e.g. elastic tubular hose or elastic tubular stockings that are a compressive fit over a limb wound to apply suitable pressure to it when the therapy is applied in this way; and

25 inflatable cuffs, sleeves, jackets, trousers, sheathes, wraps, stockings and hose that are a compressive fit over a limb wound to apply suitable pressure to it when the therapy is applied in this way.

30 Such means may each be laid out over the wound dressing to extend beyond the periphery of the backing layer of the wound dressing, and as appropriate will be adhered or otherwise secured to the skin around the wound and/or itself and as appropriate will apply compression (e.g. with elastic bandages, stockings) to a degree that is sufficient to hold the wound dressing in place in a fluid-tight seal around the periphery of the wound.

Such means may each be integral with the other components of the dressing, in particular the backing layer.

5 Alternatively, it may be permanently attached or releasably attached to the dressing, in particular the backing layer, with an adhesive film, for example, or these components may be a Velcro <sup>TM</sup>, push snap or twist-lock fit with each other.

10 The means and the dressing may be separate structures, permanently unattached to each other.

In a more suitable layout for higher positive pressures on the wound, a stiff flange or lip extends around the periphery of the proximal face of the backing layer of the wound dressing as hereinbefore defined.

15 The flange or lip is concave on its proximal face to define a peripheral channel or conduit.

It has a suction outlet that passes through the flange or lip to communicate with the channel or conduit and may be connected to a device for applying a vacuum, such as a pump or a piped supply of vacuum.

20 The backing layer may be integral with or attached, for example by heat-sealing, to the flange or lip extending around its proximal face.

25 To form the relatively fluid-tight seal or closure over a wound that is needed and to prevent passage of irrigant and/or exudate under the periphery of the wound-facing face of the wound dressing, in use of the apparatus, the dressing is set on the skin around the wound.

30 The device then applies a vacuum to the interior of the flange or lip, thus forming and maintaining a seal or closure acting at peripheral points around the wound against the positive pressure on the wound.

35 With all the foregoing means of attachment, and means for forming and maintaining a seal or closure over the wound, against positive or negative pressure on the wound at peripheral points around the wound, the wound



dressing sealing periphery is preferably of a generally round shape, such as an ellipse, and in particular circular.

5 To form the relatively fluid-tight seal or closure over a wound and around the inlet pipe(s) and outlet pipe(s) at the point at which they pass through and/or under the wound-facing face, the backing layer may be integral with these other components.

10 The components may alternatively just be a push, snap or twist-lock fit with each other, or adhered or heat-sealed together.

The or each inlet pipe or outlet pipe may be in the form of an aperture, such as a funnel, hole, opening, orifice, luer, slot or port for connection as a female member respectively to a mating end of

15 a fluid recirculation tube and/or fluid supply tube (optionally or as necessary via means for forming a tube, pipe or hose, or nozzle); or a fluid offtake tube.

20 Where the components are integral they will usually be made of the same material (for which it will be understood that materials that are listed above are amongst those that are suitable).

25 Where, alternatively, they are a push, snap or twist-lock fit, they may be of the same material or of different materials. In either case, materials that are listed above are amongst those that are suitable for all the components.

The or each pipe will generally pass through, rather than under the backing layer.

30 In such case, the backing layer may often have a rigid and/or resiliently inflexible or stiff area to resist any substantial play between the or each pipe and the or each mating tube, or deformation under pressure in any direction.

35 It may often be stiffened, reinforced or otherwise strengthened by a boss projecting distally (outwardly from the wound) around each relevant tube,

pipe or hose, or nozzle, hole, opening, orifice, luer, slot or port for connection to a mating end of a fluid recirculation tube and/or fluid supply tube or fluid offtake tube.

- 5 Alternatively or additionally, where appropriate the backing layer may have a stiff flange or lip extending around the proximal face of the backing layer to stiffen, reinforce or otherwise strengthen the backing layer.

10 The wound dressing may not comprise any integer under the backing layer in the wound in use, other than the ribs or ridges mentioned herein.

To be suitable for use, in particular to impose pressure on the wound bed,

- a) the interior of the wound dressing should conform to the wound bed, even for a wound in a highly exuding state, and  
 15 b) the wound facing face of the dressing, e.g. a fluid-inflatable module as described hereinbefore, should contact or lie very close to the wound bed.

20 In particular with relatively high concentrations of materials that are deleterious to wound healing, it may be advantageous to provide a system where wound irrigant and/or wound exudate may be distributed more evenly, or pass in a more linear path under the dressing over the wound bed.

25 Accordingly, one form of the dressing is provided with a wound filler under the backing layer.

This is favourably a resiliently flexible, e.g. elastomeric, and preferably soft, structure with good conformability to wound shape.

30 It is urged by its own resilience against the backing layer to apply gentle pressure on the wound bed.

The wound filler may be integral with the other components of the dressing, in particular the backing layer.

35

Alternatively, it may be permanently attached to them/it, with an adhesive film, for example, or by heat-sealing, e.g. to a flange or lip extending from the proximal face, so as not to disrupt the relatively fluid-tight seal or closure over the wound that is needed.

5

Less usually, the wound filler is releasably attached to the backing layer, with an adhesive film, for example, or these components may be a push, snap or twist-lock fit with each other.

- 10 The wound filler and the backing layer may be separate structures, permanently unattached to each other.

- 15 If there is a fluid-inflatable module that lies in the wound in use, such as a fluid-inflatable irrigant inlet manifold comprised in the dressing as described hereinafter in greater detail, then the wound filler may be or comprise a solid integer, favourably a resiliently flexible, e.g. elastomeric, and preferably soft, structure with good conformability to wound shape.

- 20 Examples of suitable forms of such wound fillers are foams formed of a suitable material, e.g. a resilient thermoplastic.

Preferred materials for the present wound dressing include reticulated filtration polyurethane foams with small apertures or pores.

- 25 It may also be in the form of, or comprise one or more conformable non-inflatable hollow bodies defined by a film, sheet or membrane, such as a bag, chamber, pouch or other structure, filled with a fluid or solid that urges it to the wound shape.

- 30 Examples of suitable fluids for filling such non-inflatable hollow body or bodies defined by a film, sheet or membrane include gases, such as air, nitrogen and argon, more usually air, at a small positive pressure above atmospheric; and liquids, such as water, saline.

- 35 Examples also include gels, such as silicone gels, e.g. CaviCare™ gel, or preferably cellulosic gels, for example hydrophilic cross-linked cellulosic gels,

such as Intrasilite<sup>TM</sup> cross-linked materials. Examples also include aerosol foams, where the gaseous phase of the aerosol system is air or an inert gas, such as nitrogen or argon, more usually air, at a small positive pressure above atmospheric; and solid particulates, such as plastics crumbs or beads.

5

If there is no fluid-inflatable, module the filler should be or comprise a fluid-inflatable module. It may be in the form of, or comprise one or more conformable hollow bodies defined by a film, sheet or membrane, such as a bag, chamber, pouch or other structure, filled with a fluid or solid that urges it to the wound shape.

10

It will be stimulated to change shape as appropriate and optionally at desired frequencies by inflation with fluid, followed as desired by deflation, as described hereinbefore.

15

This is capable of maintaining the pressure on the wound bed and optionally tissue surrounding the wound and/or the fluid thereover at a constant level, but more usually it is also capable of regularly or randomly (preferably cyclically) varying and/or pulsing the pressure applied to the wound, all at or near an appropriate, desired level of stress to the wound bed and optionally tissue surrounding the wound, to an appropriate, desired programme while moving fluid over the wound bed

20

The film, sheet or membrane of such a filler often has a (generally uniform) thickness similar to that of films or sheets used in conventional wound dressing backing layers.

25

That is, up to 100 micron, preferably up to 50 micron, more preferably up to 25 micron, and of 10 micron minimum thickness, and is often resiliently flexible, e.g. elastomeric, and preferably soft.

30

Such a filler is often integral with the other components of the dressing, in particular the backing layer, or permanently attached to them/it, with an adhesive film, for example, or by heat-sealing, e.g. to a flange

35

Examples of suitable fluids for inflating the hollow body or bodies defined by a film, sheet or membrane include gases, such as air, nitrogen and argon, more usually air, at a small positive pressure above atmospheric; and liquids, such as water, saline.

5

Examples also include gels, such as silicone gels, e.g. CaviCare™ gel, or preferably cellulosic gels, for example hydrophilic cross-linked cellulosic gels, such as Intrasite™ cross-linked materials. Examples also include aerosol foams, where the gaseous phase of the aerosol system is air or an inert gas, such as nitrogen or argon, more usually air, at a small positive pressure above atmospheric.

10

Of course, if the backing layer is a sufficiently conformable and/or e.g. an upwardly dished sheet, the backing layer may lie under the wound filler, rather than vice versa.

15

In this type of layout, in order for the wound filler to urge the wound dressing towards the wound bed, it will usually have to be firmly adhered or otherwise releasably attached to the skin around the wound. This is especially the case in those embodiments where the wound filler and the backing layer are separate structures, permanently unattached to each other.

20

In such a layout for deeper wounds when the therapy is applied in this way, the means for such attachment may also form and maintain a seal or closure over the wound.

25

Where the filler is over the backing layer, and the fluid inlet pipe(s) and outlet pipe(s) pass through the wound-facing face of the backing layer, they may run through or around the wound filler over the backing layer.

30

One form of the dressing is provided with a wound filler under the backing layer that is or comprises a fluid-inflatable irrigant inlet manifold, as described hereinafter in greater detail. It will be stimulated to change shape as appropriate and optionally at desired frequencies by inflation with irrigant, followed as desired by deflation.

35

This may be a resiliently flexible, e.g. elastomeric, and preferably soft, hollow body defined by a film, sheet or membrane, such as a bag, chamber, pouch or other structure, with apertures, holes, openings, orifices, slits or slots, or tubes, pipes, tubules or nozzles. It communicates with at least one inlet or outlet pipe through at least one aperture, hole, opening, orifice, slit or slot.

The fluid contained in the hollow body will then be the circulating fluid in the apparatus.

The type of the fluid-inflatable module(s) that is/are used as a component of a wound dressing may be largely determined by the depth and/or capacity of the wound.

Thus, for shallower wounds, examples of suitable such modules as a component of a wound dressing include ones that consist essentially of

- a) a shallow fluid-inflatable filler, or
- b) one or more fluid-inflatable inlet manifolds that deliver the circulating fluid directly to the wound bed, optionally with one or more outlet manifolds that collect the fluid directly from the wound.

A more suitable wound filler for deeper wounds is one which comprises

- a) a shallow fluid-inflatable filler, or
- b) one or more fluid-inflatable inlet manifolds that deliver the circulating fluid directly to the wound bed,

that at least partly surround(s) a solid integer, optionally with one or more outlet manifolds that collect the fluid directly from the wound. This may provide a system with better rigidity for convenient handling.

Where a fluid-inflatable module is or comprises a fluid-inflatable inlet manifold, it is provided with apertures admitting fluids to the wound bed under the wound dressing. These may inter alia be in the form of microapertures in a semi-permeable membrane.

Such an inlet manifold may be used with an outlet manifold. Suitable layouts of integers under the dressing include ones where either or both manifolds are regular, e.g. elliptical or circular, or irregular annular or toroidal

The inlet and/or outlet tubes, the fluid recirculation tube and the fluid supply tube, etc. may be of conventional type, e.g. of elliptical or circular cross-section, and may suitably have a uniform cylindrical bore, channel, conduit or  
5 passage throughout their length.

Depending on the desired fluid volume flow rate of irrigant and/or wound exudate from the wound, and the desired amount in recirculation, suitably the largest cross-dimension of the bore may be up to 10 mm for large torso  
10 wounds, and up to 2 mm for limb wounds.

The tube walls should suitably thick enough to withstand any positive or negative pressure on them, in particular if the volume of irrigant and/or wound exudate from the wound in recirculation is increased by continuing  
15 addition to it of wound exudate, and/or fluid passing from a cleansing fluid through a selectively permeable integer, for example the polymer film, sheet or membrane of a two-phase system, such as an dialysis unit. However, as noted below with regard to pumps, the prime purpose of such tubes is to convey fluid irrigant and exudate through the length of the apparatus flow  
20 path, rather than to act as pressure vessels. The tube walls may suitably be at least 25 micron thick.

The bore or any perforations, apertures, holes, openings, orifices, slits or slots along the pipes, etc. or in the hollow body or each of the hollow bodies  
25 may be of small cross-dimension.

They may then effectively form a macroscopic and/or microscopic filter for particulates including cell debris and micro-organisms, whilst allowing proteins and nutrients to pass through.  
30

Such tubes, pipes or hoses, etc. through and/or around the filler, whether the latter is a solid integer and/or one or more resiliently flexible or conformable hollow bodies, are described in further detail hereinbefore in connection with the inlet pipe(s) and outlet pipe(s).  
35

Returning to the flowpath of the apparatus, the means for flow switching between supply and recirculation may take any form that enables the wound simultaneously to be

- a) put into communication with the fluid reservoir but
- 5 b) closed to the fluid recirculation tube, and
- c) vice versa.

Thus, if there is only one inlet pipe that passes through and/or under the wound-facing face of the wound dressing, the fluid reservoir is connected by  
10 the fluid supply tube to the flow path via means for flow switching as desired the into a fluid recirculation tube or a fluid offtake tube.

In this case, the means for flow switching between supply and recirculation may be a regulator, such as a T- valve. This is connected in turn to two parts  
15 of a fluid recirculation tube or a fluid offtake tube and the fluid supply tube, such that the desired flow switching between supply and recirculation is achieved.

If there are two or more inlet pipes, these may be connected respectively to a fluid supply tube or fluid recirculation tube, respectively having a first  
20 regulator and a second regulator, such as a valve or other control device for admitting fluids into the wound.

The desired flow switching between supply and recirculation is achieved by respectively having the first regulator open when the second regulator is  
25 shut, and vice versa.

The means for bleeding the flowpath may be situated in any appropriate part of the apparatus that is in contact with the irrigant and/or wound exudate, but is usually within the offtake and/or recirculation tubes. However, it is often as  
30 far downstream of and away from the reservoir and the fluid supply tube as possible, so that it may be used to prime the whole of the flowpath from the fluid reservoir via the fluid supply tube.

It may be a regulator, such as a valve or other control device, e.g. a T-valve  
35 that is turned to switch between bleed and recirculation, for bleeding fluids from the apparatus, e.g. to a waste reservoir, such as a collection bag.



Alternatively, flow switching between supply and recirculation may not be desired, but rather concomitant bleeding and/or recirculation is desired.

- The latter may occur when the volume of irrigant and/or wound exudate in recirculation is increased by continuing addition to it of
- 5 a) wound exudate, and/or
  - b) fluid passing from a cleansing fluid through a selectively permeable integer, for example in a system such as a dialysis unit.

- 10 The means for bleeding the offtake and/or recirculation tubes may then be provided in the form of a regulator, such as a simple valve or other control device for admitting or blocking the passage of irrigant and/or exudate through a bleed line branching from the recirculation path.

- 15 The means for fluid cleansing may as desired be a 'single-phase system'.

- In this, the circulating fluid from the wound and the fluid reservoir passes through a self-contained system in which materials deleterious to wound healing are removed and the cleansed fluid, still containing materials that are
- 20 beneficial in promoting wound healing, is returned via the recirculation tube to the wound bed. Such systems are described in further detail hereinafter in connection with the means for fluid cleansing.

- Alternatively, where appropriate it may be provided in the form of a two-
- 25 phase system, such as a dialysis unit, or a biphasic liquid extraction unit.

- In this, the circulating fluid from the wound and the fluid reservoir passes through a system in which the fluid recirculates in indirect or (less usually, direct) contact with a second fluid (dialysate) phase, more usually a liquid, in
- 30 which materials deleterious to wound healing are removed and the cleansed fluid, still containing materials that are beneficial in promoting wound healing, is returned via the recirculation tube to the wound bed. Such systems are described in further detail hereinafter in connection with the means for fluid cleansing.

In use, typically, the means for flow switching between supply and recirculation tubes is set to admit fluid into the wound from the fluid reservoir but to close the wound to the fluid recirculation tube.

- 5 Then, any means for bleeding the offtake and/or recirculation tubes are is opened and the device for moving fluid through the wound and means for fluid cleansing is started.

The capacity of the apparatus flow path and the flow rate of irrigant and/or wound exudate from the wound will largely determine whether it is  
10 appropriate to run the device to prime the apparatus throughout the whole length of the apparatus flow path, i.e. to displace any existing fluid reservoir (often air) from the fluid recirculation path, and for how long it should be run. Typically, there is a preponderance of irrigant from the fluid reservoir over wound exudate in recirculation, so that use of the device for moving fluid  
15 through the wound is appropriate for this purpose.

It is allowed to run until the apparatus is primed throughout the whole length of the apparatus flow path.

- 20 Then, typically the means for bleeding the offtake and/or recirculation tubes is closed, and the means for flow switching between supply and recirculation tubes is set to close the wound to the fluid reservoir but to admit fluid into the wound from the fluid recirculation tube.

- 25 If the means for fluid cleansing is a two-phase system, such as a dialysis unit, or a biphasic extraction unit, the cleansing fluid is typically set in motion in contact with the surface of the selectively permeable integer, for example the polymer film; sheet or membrane. Of course, the cleansing fluid may less usually be static, and then this step is omitted.

30

As noted below in more detail, the volume of irrigant and/or wound exudate from the wound in recirculation may be increased by continuing addition to it of

- a) wound exudate, and/or

- b) fluid passing from a cleansing fluid through a selectively permeable integer, for example the polymer film, sheet or membrane of a two-phase system, such as an dialysis unit.

- 5 Additionally or alternatively, it may be desired to apply a negative pressure to the wound by means of a device for moving fluid through the wound and means for fluid cleansing applied to the fluid in recirculation in the fluid recirculation tube downstream of and away from the wound dressing.
- 10 In such case, it may be desirable to provide a system in which concomitant bleeding and/or recirculation is possible, and to make the necessary adjustments to maintain the desired balance of fluid in recirculation by means of the means for bleeding the offtake and/or recirculation tubes.
- 15 The volume of irrigant and/or wound exudate from the wound in recirculation may be decreased by continuing loss from it of fluid passing from a cleansing fluid through a selectively permeable integer, for example in a system such as a dialysis unit.
- 20 Additionally or alternatively, it may be desired to apply a positive pressure to the wound by means of a device for moving fluid through the wound and means for fluid cleansing applied to the fluid in recirculation in the fluid recirculation tube upstream of and towards the wound dressing.
- 25 The means for flow switching between supply and recirculation may be similarly provided in a form in which concomitant supply and/or recirculation is possible, and to make the necessary adjustments to maintain the desired balance of fluid in recirculation by means of the means for flow switching.
- 30 It will be appreciated that where a positive or negative pressure is to be applied to the wound, at least one hollow body in the recirculation flow path to and from the wound bed should have sufficient resilience against the pressure to allow any significant compression or decompression of the irrigant fluid to occur.

In all embodiments of the apparatus, the type and material of such bodies (which are defined by a film, sheet or membrane) that are described by way of example herein to be suitable for use in the present invention will be largely capable of this function.

5

Thus, examples of suitable materials for bodies defined by a film, sheet or membrane, such as inlet or offtake and/or recirculation tubes and structures such as bags, chambers and pouches, filled with irrigant fluid, are suitably elastically resilient thermoplastic materials that are potentially capable of this function when pressure is applied in this way.

10

The present invention in this aspect provides several advantages.

15

One is that application of a positive pressure to the wound under the backing layer may make it possible to flood the tissue underlying the wound with one or more physiologically active components.

20

This may be effected in therapeutically active amounts, to promote greater wound healing than by treatment with the fluid physiologically active component(s) alone.

20

Such physiologically active components of the exudate that are beneficial to wound healing may be e.g. be enzymes or other species and may be supplied from the dialysate of a dialytic means for fluid cleansing.

25

It is believed that using the apparatus for aspirating, irrigating and/or cleansing wounds of the present invention cyclically the effects may be further enhanced.

30

Circulating wound fluid aids in movement of biological signalling molecules involved in wound healing to locations in the wound bed that are favourable to the wound healing process and/or to cells that would otherwise not be exposed to them, e.g. in a highly exuding wound.

35

This is especially the case in those embodiments of the apparatus of this first aspect of the present invention for aspirating, irrigating and/or cleansing wounds where there is an inlet or outlet manifold from which tubules radiate

and run to the wound bed to end in openings that deliver and collect the fluid directly from the wound bed over an extended area.

5 Such materials include cytokines, enzymes, nutrients for wound cells to aid proliferation, oxygen, and other molecules that are beneficially involved in wound healing, such as growth factors, and others having beneficial effects (which may be further enhanced) in causing chemotaxis.

10 The whole length of the apparatus for aspirating, irrigating and/or cleansing wounds should be microbe-impermeable once the wound dressing is over the wound in use.

15 It is desirable that the wound dressing and the interior of the apparatus for aspirating, irrigating and/or cleansing wounds of the present invention is sterile.

20 The fluid may be sterilised in the fluid reservoir and/or the rest of the system in which the fluid recirculates, including the means for fluid cleansing, by ultraviolet, gamma or electron beam irradiation. This way, in particular reduces or eliminates contact of internal surfaces and the fluid with any sterilising agent.

Examples of other methods of sterilisation of the fluid also include e.g. the use of  
25 ultrafiltration through microapertures or micropores, e.g. of 0.22 to 0.45 micron maximum cross-dimension, to be selectively impermeable to microbes; and  
fluid antiseptics, such as solutions of chemicals, such as chlorhexidine and povidone iodine; metal ion sources, such as silver salts, e.g. silver nitrate;  
30 and hydrogen peroxide;  
although the latter involve contact of internal surfaces and the fluid with the sterilising agent.

35 It may be desirable that the interior of the wound dressing, the rest of the system in which the fluid recirculates, and/or the wound bed, even for a wound in a highly exuding state, are kept sterile after the fluid is sterilised in

the fluid reservoir, or that at least naturally occurring microbial growth is inhibited.

Thus, materials that are potentially or actually beneficial in this respect may  
5 be added to the irrigant initially, and as desired the amount in recirculation increased by continuing addition.

Examples of such materials include antibacterial agents (some of which are listed above), and antifungal agents.

10 Amongst those that are suitable are, for example triclosan, iodine, metronidazole, cetrimide, chlorhexidine acetate, sodium undecylenate, chlorhexidine and iodine.

Buffering agents, such as potassium dihydrogen phosphate/ disodium  
15 hydrogen phosphate. may be added to adjust the pH.

Local analgesics/anaesthetics, such as lidocaine/lignocaine hydrochloride, xylocaine (adrenoline, lidocaine) and/or anti-inflammatories may also be  
20 added to reduce wound pain or inflammation or pain associated with the dressing.

It is also desirable to provide a system in which physiologically active components of the exudate that are beneficial to wound healing are not removed before or after the application of fluid cleansing, e.g. by the passive  
25 deposition of materials that are beneficial in promoting wound healing, such as proteins, e.g. growth factors.

This may occur at any point at least one inlet or outlet pipe through at least one aperture, hole, opening, orifice, slit or slot.

30

The fluid contained in the hollow body may the deposition of materials that are beneficial in promoting wound healing, and consequent coating,

a) may be added to the irrigant initially, and as desired the amount in recirculation increased by continuing addition, or

b) may be used at any point or on any integer in the recirculation path in direct contact with the fluid, e.g. on the means for fluid cleansing or any desired tube or pipe.

5 Examples of coating materials for surfaces over which the circulating fluid passes include  
anticoagulants, such as heparin, and  
high surface tension materials, such as PTFE, and polyamides,  
which are useful for growth factors, enzymes and other proteins and  
10 derivatives.

The apparatus of the invention for aspirating, irrigating and/or cleansing wounds is provided with means for admitting fluids directly or indirectly to the wound under the wound dressing in the form of a fluid supply tube to a fluid  
15 reservoir.

The fluid reservoir may be of any conventional type, e.g. a tube, bag (such as a bag typically used for blood or blood products, e.g. plasma, or for infusion feeds, e.g. of nutrients), chamber, pouch or other structure, e.g. of polymer  
20 film, which can contain the irrigant fluid.

The reservoir may be made of a film, sheet or membrane, often with a (generally uniform) thickness similar to that of films or sheets used in conventional wound dressing backing layers, i.e. up to 100 micron, preferably  
25 up to 50 micron, more preferably up to 25 micron, and of 10 micron minimum thickness, and is often a resiliently flexible, e.g. elastomeric, and preferably soft, hollow body.

In all embodiments of the apparatus the type and material of the tubes throughout the apparatus of the invention for aspirating, irrigating and/or  
30 cleansing wounds and the fluid reservoir will be largely determined by their function.

To be suitable for use, in particular on chronic timescales, the material should  
35 be non-toxic and biocompatible, inert to any active components, as appropriate of the irrigant from the fluid reservoir and/or wound exudate in

the apparatus flow path, and, in any use of a two-phase system dialysis unit, of the dialysate that moves into the circulating fluid in the apparatus.

5 When in contact with irrigant fluid, it should not allow any significant amounts of extractables to diffuse freely out of it in use of the apparatus.

It should be sterilisable by ultraviolet, gamma or electron beam irradiation and/or with fluid antiseptics, such as solutions of chemicals, fluid- and microbe-impermeable once in use, and flexible.

10

Examples of suitable materials for the fluid reservoir include synthetic polymeric materials, such as polyolefins, such as polyethylene, e.g. high-density polyethylene and polypropylene.

15

Suitable materials for the present purpose also include copolymers thereof, for example with vinyl acetate and mixtures thereof. Suitable materials for the present purpose further include medical grade poly(vinyl chloride).

20

Notwithstanding such polymeric materials, the fluid reservoir will often have a stiff area to resist any substantial play between it and components that are not mutually integral, such as the fluid supply tube towards the wound dressing, and may be stiffened, reinforced or otherwise strengthened, e.g. by a projecting boss.

25

The device for moving fluid through the wound and means for fluid cleansing may be any appropriate for this purpose, and may act at any appropriate point for this purpose.

30

It may apply a positive or negative pressure to the wound, although its prime purpose is to move fluid (irrigant from the fluid reservoir and/or wound exudate through the length of the apparatus flow path, rather than to apply a positive or negative pressure to the wound.

35

If applied to the fluid in recirculation in the fluid recirculation tube upstream of and towards the wound dressing and/or the fluid in the fluid supply tube towards the wound dressing (optionally or as necessary via means for flow



switching between supply and recirculation), it will usually apply positive pressure (i.e. above-atmospheric pressure) to the wound bed and optionally tissue surrounding the wound.

- 5 Often the means for fluid cleansing is (most appropriately for its purpose) downstream of the wound dressing, and provides the highest resistance in the flow path. This is especially the case where the means for fluid cleansing is a single-phase system, e.g. with ultrafiltration through microapertures or micropores, thus enhancing applied positive pressure to the wound.
- 10 Where the device is applied to the fluid in recirculation in the fluid recirculation tube and/or the fluid in the fluid offtake tube downstream of and away from the wound dressing, it will usually apply negative pressure (i.e. below-atmospheric pressure or vacuum) to the wound bed and optionally tissue surrounding the wound.

- 15 Again, often the means for fluid cleansing is (most appropriately for its purpose) downstream of the wound dressing, and provides the highest resistance in the flow path, thus enhancing applied negative pressure to the wound.

- 20 The following types of pump may be used as desired:

reciprocating pumps, such as:

- shuttle pumps - with an oscillating shuttle mechanism to move fluids at  
 25 rates from 2 to 50 ml per minute;
- diaphragm pumps - where pulsations of one or two flexible diaphragms  
 displace liquid while check valves control the direction of  
 the fluid flow.
- piston pumps - where pistons pump fluids through check valves, in  
 30 particular for positive and/or negative pressure on the  
 wound bed;

rotary pumps, such as:

- 35 centrifugal pumps  
 flexible impeller

- pumps - where elastomeric impeller traps fluid between impeller blades and a moulded housing that sweeps fluid through the pump housing.
- progressing cavity pumps - with a cooperating screw rotor and stator, in particular for higher-viscosity and particulate-filled exudate;
- rotary vane pumps - with rotating vaned disk attached to a drive shaft moving fluid without pulsation as it spins. The outlet can be restricted without damaging the pump.
- peristaltic pumps - with peripheral rollers on rotor arms acting on a flexible fluid circulation tube to urge fluid current flow in the tube in the direction of the rotor.

- The type and/or capacity of the device will be largely determined by
- a) the appropriate or desired fluid volume flow rate of irrigant and/or wound exudate from the wound, and
  - b) whether it is appropriate or desired to apply a positive or negative pressure to the wound bed, and the level of such pressure to the wound bed
- for optimum performance of the wound healing process, and by factors such as portability, power consumption and isolation from contamination.

Such a device may also suitably be one that is capable of pulsed, continuous, variable, reversible and/or automated and/or programmable fluid movement. It may in particular be a pump of any of these types.

In practice, even from a wound in a highly exuding state, such a rate of exudate flow is only of the order of up to 75 microlitres / cm<sup>2</sup> / hr (where cm<sup>2</sup> refers to the wound area), and the fluid can be highly mobile (owing to the proteases present). Exudate levels drop and consistency changes as the wound heals, e.g. to a level for the same wound that equates to 12.5 – 25 microlitres / cm<sup>2</sup> / hr.

Where materials deleterious to wound healing are removed by a two-phase system (see below.), such as a dialysis unit, fluid is also potentially lost to the system through the means for fluid cleansing.

This may occur, e.g. through a dialysis polymer film, sheet or membrane which is also permeable to water, in addition to materials deleterious to wound healing.

5

The balance of fluid in recirculation may thus further decrease, but may be adjusted to minimise this undesired loss in a routine manner as described hereinbefore.

10 Hence, it will be seen that the circulating fluid from the wound will typically contain a preponderance of irrigant over wound exudate in recirculation from the fluid reservoir.

15 The type and/or capacity of the device will thus be largely determined in this respect by the appropriate or desired fluid volume flow rate of irrigant, rather than that of exudate, from the wound.

In practice, such a rate of flow of total irrigant and/or wound exudate will be of the order of 1 to 1000, e.g. 3 to 300, and less preferably 1 to 10 ml / cm<sup>2</sup> / 24 hour, where the cm<sup>2</sup> refers to the wound area.

20

The volume of irrigant and/or wound exudate in recirculation may vary over a wide range, but will typically be e.g. 1 to 8 l. (for example for large torso wounds), 200 to 1500 ml (for example for axillary and inguinal wounds), and 0.3 to 300 ml for limb wounds when the therapy is applied in this way.

25

In practice, suitable pressures are of the order of up to 25% atm such as up to 10% atm. positive or negative pressure on the wound bed, the apparatus being operated as a closed recirculating system.

30 The higher end of these ranges are potentially more suitable for hospital use, where relatively high % pressures and/or vacua may be used safely under professional supervision.

35 The lower end is potentially more suitable for home use, where relatively high % pressures and/or vacua cannot be used safely without professional supervision, or for field hospital use.

The device may be a peristaltic pump or diaphragm pump, e.g. preferably a small portable diaphragm or peristaltic pump. These are preferred types of pump, in order in particular to reduce or eliminate contact of internal surfaces and moving parts of the pump with (chronic) wound exudate, and for ease of cleaning.

It may suitably be one that applies positive pressure to the wound and/or the means for fluid cleansing.

A preferred pump when the applied pressure is positive is a peristaltic pump, e.g. a small, portable peristaltic pump, mounted upstream of the means for fluid cleansing.

Where the pump is a peristaltic pump, this may be e.g. an Instech Model P720 miniature peristaltic pump, with a flow rate: of 0.2 – 180ml/hr and a weight of < 0.5 k. This is potentially useful for home and field hospital use.

The pump may suitably be one that applies negative pressure to the wound and/or the means for fluid cleansing. A preferred pump when the applied pressure is negative is a diaphragm pump, e.g. a small, portable diaphragm pump, mounted downstream of the dressing or the means for fluid cleansing.

Where the pump is a diaphragm pump, and preferably a small portable diaphragm pump, the one or two flexible diaphragms that displace liquid may each be, for example a polymer film, sheet or membrane, that is connected to means for creating the pulsations. This may be provided in any form that is convenient, inter alia as an electromechanical transducer, a core of a solenoid or a ferromagnetic integer and coil in which the direction of current flow alternates, a rotary cam and follower, and so on.

The outlet from the dressing passes to the means for fluid cleansing for removal of materials deleterious to wound healing from wound exudate, and in turn to the fluid recirculation tube(s).

The apparatus of the invention for aspirating, irrigating and/or cleansing wounds is provided with means for fluid cleansing, which may be

- a) a single-phase system, such as an ultrafiltration unit, or a chemical absorption and/or adsorption unit; or
- b) a two-phase system, such as a dialysis unit, or a biphasic extraction unit.

5

In the former, circulating fluid from the wound and the fluid reservoir passes through a self-contained system in which materials deleterious to wound healing are removed and the cleansed fluid, still containing materials that are beneficial in promoting wound healing are returned to the wound.

10

The single-phase system may be of any conventional type.

15

Examples of the means for fluid cleansing in such a system include a macro- or microfiltration unit, which appropriately comprises one or more macroscopic and/or microscopic filters.

These are to retain particulates, e.g. cell debris and micro-organisms, allowing proteins and nutrients to pass through.

20

Alternatively, they also include an ultrafiltration unit, such as a one in which the cleansing integer is a filter for materials deleterious to wound healing, for example a high throughput, low protein-binding polymer film, sheet or membrane which is selectively impermeable to materials deleterious to wound healing, which are removed and the cleansed fluid, still containing

25

materials that are beneficial in promoting wound healing is passed by it.

The membrane may preferably be of a hydrophilic polymeric material, such as a cellulose acetate – nitrate mixture, polyvinylidene chloride, and, for example hydrophilic polyurethane.

30

Examples of less preferred materials include hydrophobic materials also including polyesters, such as polycarbonates, PTFE, and polyamides, e.g. 6-6 and 6-10, and hydrophobic polyurethanes, and quartz and glass fibre.

It has microapertures or micropores, the maximum cross-dimension of which will largely depend on the species that are to be selectively removed in this way and those to which it is to be permeable.

5 The former may be removed with microapertures or micropores, e.g. typically with a maximum cross-dimension in the range of 20 to 700 micron, e.g. 20 to 50 nm (for example for undesired proteins), 50 to 100 nm, 100 to 250 nm, 250 to 500 nm and 500 to 700 nm.

10 The filter integer may be a flat sheet or a membrane of a polymeric material in a more convoluted form, e.g. in the form of elongate structure, such as pipes, tubules, etc.

15 The system may be a chemical adsorption unit, for example one in which a particulate, such as a zeolite, or a layer, e.g. of a functionalised polymer has sites on its surface that are capable of removing materials deleterious to wound healing on passing the circulating fluid from the wound and the fluid reservoir over them.

20 The materials may be removed, e.g. by destroying or binding the materials that are deleterious to wound healing, by, for example chelators and/or ion exchangers, degraders, which may be enzymes.

25 Examples of such also include less specific chemical adsorption units, for example one in which a physical absorbent, such as activated carbon or a zeolite, has non-specific sites on its surface that are capable of removing materials deleterious to wound healing on passing the circulating fluid from the wound and the fluid reservoir over them.

30 The cleansing integer, for example the polymer film, sheet or other chemical absorption and/or adsorption means, etc should of course be capable of removing materials deleterious to wound healing at a practical rate for a given capacity of the apparatus flow path and the flow rate of irrigant.

35 In the two-phase system, circulating fluid from the wound and the fluid reservoir in indirect or (less usually, direct) contact with a second fluid (dialysate) phase, more usually a liquid.

Thus, in one form, a biphasic liquid extraction unit, the second fluid phase is (usually) a liquid that is immiscible with the circulating fluid from the dressing, over a surface of which the circulating fluid passes in direct contact with the cleansing fluid. Materials deleterious to wound healing are removed into the dialysate, and the cleansed fluid, still containing materials that are beneficial in promoting wound healing, is returned via the recirculation tube to the wound bed.

Examples of such means for fluid cleansing include those wherein the second fluid (dialysate) phase is perfluorodecalin and like materials

Alternatively, where appropriate it may be provided in a form in which the two fluids (recirculation fluid and dialysate) are separated by a significantly two-dimensional integer, for example a polymer film, sheet or membrane or hollow fibre or filament that is permeable to materials in the circulating fluid in the apparatus.

Again, materials deleterious to wound healing are removed into the dialysate, and the cleansed fluid, still containing materials that are beneficial in promoting wound healing, is returned via the recirculation tube to the wound bed.

In either form in which the two-phase system, such as a dialysis unit, is provided, in use typically the dialysate moves past the circulating fluid in the apparatus in a co- or preferably counter-current direction.

Pumps, such as peristaltic pumps, and/or valves control the direction of the two fluid flows.

However, the cleansing fluid may less usually be static, although this may not provide a system with sufficient (dynamic) surface area to remove materials deleterious to wound healing from wound exudate at a practical rate.

Typical dialysate flow rates in a dialytic means for fluid cleansing in the present apparatus for aspirating, irrigating and/or cleansing wounds are

those used in the conventional type of two-phase system, such as a dialysis unit for systemic therapy.

5 The integer may be a film, sheet or membrane, often of the same type, and of the same (generally uniform) thickness, as those used in conventional two-phase system, such as a dialysis unit for systemic therapy.

10 The film, sheet or membrane may be substantially flat, and depending on any pressure differential across it may require other materials on or in it to stiffen, reinforce or otherwise strengthen it.

15 However, this may not provide a system with sufficient functional surface area to remove materials deleterious to wound healing from wound exudate at a practical rate.

20 To be suitable for use, in particular in chronic wound dialysis, with relatively high concentrations of materials that are deleterious to wound healing, it may be advantageous to provide a system in which the film, sheet or membrane of a polymeric material is in a more convoluted form.

25 This may be in the form of elongate structures, such as pipes, tubes hollow fibres or filaments or tubules of a round cross-section, e.g. elliptical or circular, e.g. in a parallel array with spaces therebetween.

30 The wound irrigant and/or wound exudate may recirculate through the inside and the cleansing fluid may pass into the spaces between adjacent pipes, tubes or tubules in a co- or preferably counter-current direction, or vice versa.

35 Again, materials deleterious to wound healing are removed into the dialysate, and the cleansed fluid, still containing materials that are beneficial in promoting wound healing, is returned via the recirculation tube to the wound.

Where the means for fluid cleansing is a two-phase system, e.g. in the form of a dialysis unit, or a biphasic extraction unit, the circulating fluid from the wound and the fluid reservoir passes across one surfaces of a significantly



two-dimensional integer, for example a polymer film, sheet or membrane which is selectively permeable to materials deleterious to wound healing.

- 5 These are removed by passing a cleansing fluid across the other surface of the integer. The integer may be a film, sheet or membrane that is selectively permeable to the foregoing materials deleterious to wound healing.

- Examples of these as above include
- oxidants, such as free radicals, e.g. peroxide and superoxide;
  - 10 iron II and iron III;
  - all involved in oxidative stress on the wound bed;
  - proteases, such as serine proteases, e.g. elastase and thrombin; cysteine proteases; matrix metalloproteases, e.g. collagenase; and carboxyl (acid) proteases;
  - 15 endotoxins, such as lipopolysaccharides;
  - bacterial autoinducer signalling molecules, such as homoserine lactone derivatives, e.g. oxo-alkyl derivatives;
  - inhibitors of angiogenesis such as thrombospondin-1 (TSP-1), plasminogen activator inhibitor, or angiostatin (plasminogen fragment);
  - 20 pro-inflammatory cytokines such as tumour necrosis factor alpha ( $TNF_{\alpha}$ ) and interleukin 1 beta ( $IL-1\beta$ ),
  - and
  - inflammatories, such as lipopolysaccharides, and e.g. histamine.

- 25 Examples of suitable materials for the film, sheet or membrane (typically in the form of conformable hollow bodies defined by the film, sheet or membrane, such as the structures described hereinbefore) include natural and synthetic polymeric materials.

- 30 The membrane may be of one or more hydrophilic polymeric materials, such as a cellulose derivative, e.g. regenerated cellulose, a cellulose mono-, di- or tri- esters, such as cellulose mono-, di- or tri-acetate, benzyl cellulose and Hemophan, and mixtures thereof.

- 35 Examples of other materials include hydrophobic materials, such as aromatic polysulphones, polyethersulphones, polyetherether-sulphones, polyketones,

polyetherketones and polyetherether-ketones, and sulphonated derivatives thereof, and mixtures thereof.

5 Examples of other materials include hydrophobic materials, such as polyesters, such as polycarbonates and polyamides, e.g. 6-6 and 6 – 10; polyacrylates, including, e.g. poly(methyl methacrylate), polyacrylonitrile and copolymers thereof, for example acrylonitrile - sodium metallosulphonate copolymers; and poly(vinylidene chloride).

10 Suitable materials for the present membranes include \*thermoplastic polyolefins, such as polyethylene e.g. high-density polyethylene, polypropylene, copolymers thereof, for example with vinyl acetate and polyvinyl alcohol, and mixtures thereof.

15 The dialysis membrane should have a molecular weight cut off (MWCO) chosen to allow selective perfusion of species deleterious to wound healing that have been targeted for removal from the wound. For example, perfusion of the serine protease elastase (molecular weight 25900 Dalton) would require a membrane with MWCO >25900 Dalton. The MWCO threshold can  
20 be varied to suit each application between 1 and 3000000 Dalton.

Preferably, the MWCO should be as close as possible to this weight to exclude interference by larger competitor species.

25 For example, such a membrane with MWCO >25900 Dalton does not allow any significant amounts of the antagonist to elastase, alpha-1-antitrypsin (AAT) (molecular weight 54000 Dalton), which occurs naturally in wounds, to diffuse freely out of the wound fluid into the dialysate.

30 The inhibitor, which is beneficial in promoting chronic wound healing, remains in contact with the wound bed, and can act beneficially on it, whilst the elastase that is deleterious to wound healing is removed.

35 Such use of the present apparatus is, e.g. favourable to the wound healing process in chronic wounds, such as diabetic foot ulcers, and especially decubitus pressure ulcers.

As noted hereinafter, antagonists, for example degrading enzymes, or sequestering agents for elastase on the dialysate side of the membrane, may be used to enhance the removal of this protease from wound exudate.

- 5    Where it is desired to remove several different materials that are deleterious to wound healing, it may be advantageous to provide a system of modules in series, each of which removes a different material.

This allows incompatible cleansing materials to be used on the same fluid and/or wound exudates.

10

Preferably any such system is a conventional automated, programmable system which can cleanse the wound irrigant and/or wound exudate with minimal supervision.

- 15    As noted above in more detail, fluid passes from a cleansing fluid through a selectively permeable integer.

This may be the typical permeable polymer film, sheet or membrane of a two-phase system, such as a dialysis unit.

20

Additionally, solutes or disperse phase species will pass from the dialysate into the irrigant and/or wound exudate through the dialysis polymer film, sheet or membrane.

- 25    This property may be used to perfuse materials beneficial to wound healing into the irrigant and/or exudate from a dialysate.

In this less conventional type of infusion feed, a broad spectrum of species will usually pass into the exudate and/or irrigant fluid from the dialysate.

30

These include

ionic species, such as bicarbonate;

vitamins, such as ascorbic acid (vitamin C) and vitamin E, and stable derivatives thereof, and mixtures thereof; to relieve oxidative stress on the

35

wound bed;

pH buffering agents, such as potassium dihydrogen phosphate/ disodium hydrogen phosphate,

local analgesics/anaesthetics, such as lidocaine/lignocaine hydrochloride and xylocaine (adrenoline lidocaine) and/or anti-inflammatories, to reduce wound

5 pain or inflammation or pain associated with the dressing

nutrients to aid proliferation of wound cells, such as amino acids, sugars, low molecular weight tissue building blocks and trace elements; and other cell culture medium species; and

gases, such as air, nitrogen, oxygen and/or nitric oxide.

10

For the purposes of fluid cleansing in the apparatus of the present invention, both the single-phase system, such as an ultrafiltration unit, and two-phase system, such as a dialysis unit, may have captive (non-labile, insoluble and/or immobilised) species such as the following, bound to an insoluble and/or immobilised) substrate over and/or through which the irrigant and/or

15

wound exudate from, the wound dressing passes in turn to the fluid recirculation tube(s):

antioxidants and free radical scavengers, such as 3-hydroxytyramine (dopamine), ascorbic acid (vitamin C), vitamin E and glutathione, and stable derivatives thereof, and mixtures thereof; to relieve oxidative stress on the wound bed;

20

metal ion chelators and/or ion exchangers, such as transition metal ion chelators, such as iron III chelators (Fe III is involved in oxidative stress on the wound bed.), such as desferrioxamine (DFO), 3-hydroxytyramine (dopamine),

25

iron III reductants;

protease inhibitors, such as TIMPs and alpha 1-antitrypsin (AAT); serine protease inhibitors, such as 4-(2-aminoethyl)-benzene sulphonyl fluoride (AEBSF, PefaBloc) and  $N\alpha$ -*p*-tosyl-L-lysine chloro-methyl ketone (TLCK) and  $\epsilon$ -aminocaproyl-*p*-chlorobenzylamide; cysteine protease inhibitors; matrix metalloprotease inhibitors; and carboxyl (acid) protease inhibitors;

30

sacrificial redox materials that are potentially or actually beneficial in promoting wound healing, by the removal of materials that trigger the expression into wound exudate of redox-sensitive genes that are deleterious to wound healing;

35

autoinducer signalling molecule degraders, which may be enzymes; and anti-inflammatory materials to bind or destroy lipopolysaccharides, e.g. peptidomimetics

- 5 Other physiologically active components of the exudate that are deleterious to wound healing may be removed in this way.

These may be removed with suitable chelators and/or ion exchangers, degraders, which may be enzymes, or other species.

10

The following types of functionalised substrate has sites on its surface that are capable of removing materials deleterious to wound healing on passing the circulating fluid from the wound and the fluid reservoir over them: heterogeneous resins, for example silica-supported reagents such as:

15

metal scavengers,

3-(diethylenetriamino)propyl-functionalised silica gel

2-(4-(ethylenediamino)benzene)ethyl-functionalised silica gel

3-(mercapto)propyl-functionalised silica gel

3-(1-thioureido)propyl-functionalised silica gel

20

triamine tetraacetate-functionalised silica gel

or electrophilic scavengers,

4-carboxybutyl-functionalised silica gel

4-ethyl benzenesulfonyl chloride-functionalised silica gel

25

propionyl chloride-functionalised silica gel

3-(isocyano)propyl-functionalised silica gel

3-(thiocyano)propyl-functionalised silica gel

3-(2-succinic anhydride)propyl-functionalised silica gel

3-(maleimido)propyl-functionalised silica gel

30

or nucleophilic scavengers,

3-aminopropyl-functionalised silica gel

3-(ethylenediamino)-functionalised silica gel

2-(4-(ethylenediamino)propyl-functionalised silica gel

35

3-(diethylenetriamino)propyl-functionalised silica gel

4-ethyl-benzenesulfonamide-functionalised silica gel

2-(4-toluenesulfonyl hydrazino)ethyl-functionalised silica gel  
 3-(mercapto)propyl-functionalised silica gel  
 dimethylsiloxo-functionalised silica gel

- 5 or base or acid scavengers,  
 3-(dimethylamino)propyl-functionalised silica gel  
 3-(1,3,4,6,7,8-hexahydro-2H-pyrimido-[1,2- $\alpha$ ]pyrimidino)propyl-functionalised  
 silica gel  
 3-(1-imidazol-1-yl)propyl-functionalised silica gel  
 10 3-(1-morpholino)propyl-functionalised silica gel  
 3-(1-piperazino)propyl-functionalised silica gel  
 3-(1-piperidino)propyl-functionalised silica gel  
 3-(4,4'-trimethyldipiperidino)propyl-functionalised silica gel  
 2-(2-pyridyl)ethyl-functionalised silica gel  
 15 3-(trimethylammonium)propyl-functionalised silica gel

- or the reagents,  
 3-(1-cyclohexylcarbodiimido)propyl-functionalised silica gel  
 TEMPO-functionalised silica gel  
 20 2-(diphenylphosphino)ethyl-functionalised silica gel  
 2-(3,4-cyclohexyldiol)propyl-functionalised silica gel  
 3-(glycidoxo)propyl-functionalised silica gel  
 2-(3,4-epoxycyclohexyl)propyl-functionalised silica gel  
 1-(allyl)methyl-functionalised silica gel  
 25 4-bromopropyl-functionalised silica gel  
 4-bromophenyl-functionalised silica gel  
 3-chloropropyl-functionalised silica gel  
 4-benzyl chloride-functionalised silica gel  
 2-(carbomethoxy)propyl-functionalised silica gel  
 30 3-(4-nitrobenzamido)propyl-functionalised silica gel  
 3-(ureido)propyl-functionalised silica gel

or any combinations of the above.

- 35 The use of such captive (non-labile, insoluble and/or immobilised) species,  
 such as the foregoing, bound to an insoluble and immobilised) substrate over

and/or through which the irrigant and/or wound exudate from, the wound dressing passes has been described hereinbefore as suitable for the means for fluid cleansing.

- 5 However, they may additionally, where appropriate, be used in any part of the apparatus that is in contact with the irrigant and/or wound exudate, but often within the dressing, for removal of materials deleterious to wound healing from wound.

- 10 A backing layer in the wound dressing with ribs or ridges may be used to assist in channelling fluid across a larger area over a longer dwell time, and hence improve the cleansing of the irrigant in the wound dressing.

- 15 The means for fluid cleansing may additionally, where appropriate, comprise one or more macroscopic and/or microscopic filters.

These are to retain particulates, e.g. cell debris and micro-organisms, allowing proteins and nutrients to pass through.

- 20 Alternatively, a less conventional type of two-phase system (see above), such as a dialysis unit, may be used as the means for fluid cleansing. In this type, the dialysis polymer film, sheet or membrane is not an integer selectively permeable to materials deleterious to wound healing, such as proteases, such as serine proteases, e.g. elastase and thrombin; cysteine
- 25 protease; matrix metalloproteases, e.g. collagenase; and carboxyl (acid) proteases; endotoxins, such as lipopolysaccharides; inhibitors of angiogenesis such as thrombospondin-1 (TSP-1), plasminogen activator inhibitor, or angiostatin (plasminogen fragment)
- 30 pro-inflammatory cytokines such as tumour necrosis factor alpha ( $\text{TNF}_\alpha$ ) and interleukin 1 beta ( $\text{IL-1}\beta$ ); oxidants, such as free radicals, e.g. , e.g. peroxide and superoxide; and metal ions, e.g. iron II and iron III; all involved in oxidative stress on the wound bed.

It will however also permit components of the exudate from a wound and/or irrigant fluid that may be larger or smaller molecules, but are beneficially involved in wound healing to pass into and through it.

- 5 In the dialysate, or preferably in one or more solid structural integers with at least one surface in contact with the dialysate, in the means for fluid cleansing, there are one or more materials that can remove materials deleterious to wound healing from wound exudate, by being antagonists to such species, for example enzymes or others, such as
- 10 protease inhibitors, such as serine protease inhibitors, such as 4-(2-aminöethyl)-benzene sulphonyl fluoride (AEBSF, PefaBloc) and  $N_{\alpha}$ -*p*-tosyl-L-lysine chloromethyl ketone (TLCK) and  $\epsilon$ -aminocaproyl-*p*-chlorobenzylamide; cysteine protease inhibitors; matrix metalloprotease inhibitors; and carboxyl (acid) protease inhibitors;
- 15 binders and/or degraders, such as anti-inflammatory materials to bind or destroy lipopolysaccharides, e.g. peptidomimetics; anti-oxidants, such as 3-hydroxytyramine (dopamine), ascorbic acid (vitamin C), vitamin E and glutathione, and stable derivatives thereof, and mixtures thereof; to relieve oxidative stress on the wound bed; and
- 20 chelators and/or ion exchanges, such as desferrioxamine (DFO), 3-hydroxytyramine (dopamine),

- They further include peptides (including cytokines, e.g. bacterial cytokines, such as  $\alpha$ -amino- $\gamma$ -butyrolactone and L-homocarnosine); and
- 25 sacrificial redox materials that are potentially or actually beneficial in promoting wound healing, such as iron III reductants; and/or regeneratable materials of this type, such as glutathione redox systems; and other physiologically active components.

- 30 In use of the two-phase system dialysis unit, of this less conventional type, a broad spectrum of species will usually pass into the dialysate from the exudate.

- Some (mainly ionic) species will pass from the dialysate into the irrigant
- 35 and/or wound exudate through the dialysis polymer film, sheet or membrane



that is not very selectively permeable to materials deleterious to wound healing.

5 The components of the exudate from a wound and/or irrigant fluid will diffuse freely to and fro through it.

10 If (preferably) none of the dialysate is voided to waste, e.g. to a collection bag, a steady state concentration equilibrium is eventually set up between the dialysate and the irrigant and/or wound exudate, which is 'topped up' from the wound dressing.

Circulating wound fluid aids in the quicker attainment of this equilibrium of materials beneficial in promoting wound healing.

15 It also returns them to the site where they can be potentially of most benefit, i.e. the wound bed.

20 The target materials deleterious to wound healing also pass into the dialysate from the exudate through the dialysis polymer film, sheet or membrane that is not very selectively permeable to materials deleterious to wound healing.

25 Unlike the other components of the exudate from a wound and/or irrigant fluid, the target materials deleterious to wound healing come into contact with the dialysate, or preferably with one or more solid structural integers with at least one surface in the dialysate, and are removed by the appropriate antagonists, binders and/or degraders, chelators and/or ion exchangers and redox agents, etc. The cleansed fluid, still containing some materials that are beneficial in promoting wound healing, is returned to the recirculation tube.

30

Unlike the other components of the exudate from a wound and/or irrigant fluid the target materials are constantly removed from the dialysate.

35 Very little of these species will pass from the dialysate into the irrigant and/or wound exudate, and a steady state concentration equilibrium is not set up, even if the species are constantly 'topped up' from the wound dressing.

It is believed that circulating wound fluid aids in removal from recirculation of the materials deleterious to wound healing from wound exudate, whilst retaining materials that are beneficial in promoting wound healing in contact with the wound.

5

A particular advantage of this form of the two-phase system, is that where a material that can remove materials deleterious to wound healing from wound exudate is (cyto)toxic or bioincompatible, or not inert to any components that are beneficial in promoting wound healing, the system does not allow any significant amounts of antagonist to diffuse freely out of the dialysate into the irrigant fluid. The active material can act beneficially on the fluid however.

10

The film sheet or membrane is preferably a dialysis membrane of molecular weight cut off (MWCO) (as conventionally defined) chosen to allow perfusion of species targeted for sequestration or destruction.

15

For example, sequestration of the serine protease elastase (molecular weight 25900 Dalton) would require a membrane with MWCO >25900 Dalton.

The MWCO threshold can be varied to suit each application between 1 and 3000000 Dalton. Preferably, the MWCO should be as close as possible to this weight to exclude sequestering interference by larger competitor species.

20

Both the single-phase system, such as an ultrafiltration unit, and two-phase system, such as a dialysis unit, may be in modular form that is relatively easily demountable from the apparatus of the invention. The system may suitably comprise one or more such modules.

25

The conduits through which respectively

- a) the irrigant and/or wound exudate passes from the wound dressing and
- b) the cleansed fluid, still containing materials that are beneficial in promoting wound healing, is returned to the recirculation tube, and
- c) (in the case where the means is provided in the form of a two-phase system, such as an dialysis unit) through which the cleansing fluid enters and exits the means

30

preferably have means for, on module disconnection and withdrawal,

35

- i) switching off the flow and

- ii) providing an immediate fluid-tight seal or closure over the ends of the conduits and the cooperating tubes in the rest of the apparatus of the invention so exposed,  
to prevent continuing passage of irrigant and/or exudate and cleansed fluid,  
5 and cleansing fluid.

The apparatus of the invention for aspirating, irrigating and/or cleansing wounds is provided with means for bleeding the offtake and/or recirculation tubes, such as a regulator, such as a valve or other control device for  
10 bleeding fluids from the wound.

The device for moving fluid through the wound and means for fluid cleansing is used to move irrigant to the wound dressing and apply the desired positive or negative pressure on the wound bed.

15 The desired balance of fluid in recirculation tube will typically be regulated by means of

- a) the means for bleeding the offtake and/or recirculation tubes,  
b) the means for flow switching between supply and recirculation, and/or  
20 c) the means for moving fluid over the wound bed and through the means for fluid cleansing,  
as appropriate.

Thus, e.g. if

- 25 a) the apparatus for aspirating, irrigating and/or cleansing wounds is a single-phase system, such as an ultrafiltration unit,  
b) the wound is not in a highly exuding state and  
c) it is not appropriate or desired to admit fluid into the wound from the fluid reservoir,  
30 there is no or negligible change in the balance of fluid in recirculation.

Once it has been primed throughout, e.g. to the desired positive or negative pressure on the wound bed, the apparatus may be operated as a closed recirculating system.

35

The means for flow switching between supply and recirculation tubes is set to close the wound to the fluid reservoir via the fluid supply tube, and the means for bleeding the offtake and/or recirculation tubes are also closed.

5 If

- a) the apparatus for aspirating, irrigating and/or cleansing wounds is a single-phase system, such as an ultrafiltration unit,
  - b) the wound is in a highly exuding state and/or
  - c) it is appropriate or desired to admit fluid into the wound from the fluid
- 10 reservoir,

there is a positive change in the balance of fluid in recirculation.

Once it has been primed throughout, e.g. to the desired positive or negative pressure on the wound bed, the apparatus cannot be operated as a closed

15 recirculating system, without the pressure to the wound bed increasing, possibly undesirably.

The means for bleeding the offtake and/or recirculation tubes must be opened to some extent to relieve positive pressure on the wound bed. The

20 bleed-off may be voided to waste, e.g. to a collection bag.

Materials that are beneficial in promoting wound healing may be lost to the site where they can be potentially of most benefit, i.e. the wound bed, when the therapy is applied in this way.

25

However, the balance of fluid in recirculation may be routinely adjusted to minimise this undesired loss.

The factors that determine the balance of fluid in recirculation in an apparatus

30 with a two-phase system means for fluid cleansing in the form of a dialysis unit, or a biphasic extraction unit have been described hereinbefore in detail hereinbefore.

It is sufficient to note here that at some point after steady state recirculation

35 established through the length of the apparatus flow path, it may be

necessary that any bleed valve is opened, if overall the fluid level is increasing by transfer from the dialysate to an undesirable extent.

- 5 Other combinations, and the necessary adjustments to maintain the desired balance of fluid in recirculation tube by means of
- a) the means for bleeding the offtake and/or recirculation tubes,
  - b) the means for flow switching between supply and recirculation, and/or
  - c) the means for moving fluid
- will be apparent to the skilled person.

10 The outlet from the means for bleeding the offtake and/or recirculation tubes may be collected and monitored and used to diagnose the status of the wound and/or its exudate.

15 The waste reservoir may be of any conventional type, e.g. a tube, bag (such as a bag typically used as an ostomy bag), chamber, pouch or other structure, e.g. of polymer film, which can contain the irrigant fluid that has been bled off. In all embodiments of the apparatus, the type and material of the waste reservoir will be largely determined by its function. To be suitable  
20 for use, the material need only be fluid-impermeable once in use, and flexible.

Examples of suitable materials for the fluid reservoir include synthetic polymeric materials, such as polyolefins, such as poly (vinylidene chloride).

25 Suitable materials for the present purpose also include polyethylene, e.g. high-density polyethylene, polypropylene, copolymers thereof, for example with vinyl acetate and mixtures thereof.

30 In a second aspect of the present invention there is provided a conformable wound dressing, characterised in that it comprises a backing layer with a wound-facing face which is capable of forming a relatively fluid-tight seal or closure over a wound and has  
at least one inlet pipe for connection to a fluid supply tube, which passes  
35 through and/or under the wound-facing face, and

at least one outlet pipe for connection to a fluid offtake tube, which passes through and/or under the wound-facing face, the point at which the or each inlet pipe and the or each outlet pipe passes through and/or under the wound-facing face forming a relatively fluid-tight seal or closure over the wound; and means for applying stress to the wound bed and optionally the tissue surrounding the wound.

The dressing is advantageously provided for use in a bacteria-proof pouch.

Examples of suitable forms of such wound dressings are as described by way of example hereinbefore.

It is an object of the present invention

- c) to obviate at least some of the disadvantages of known aspiration and/or irrigation therapies, and
- d) to provide a system of therapy which
  - i) can remove materials deleterious to wound healing from wound exudate, whilst retaining materials that are beneficial in promoting wound healing in contact with the wound bed, and/or
  - ii) which allows fluids containing active amounts of materials that are beneficial in promoting wound healing to pass into and/or through the wound in contact with the wound bed.

Thus, in a third aspect of the present invention there is provided a method of treating wounds to promote wound healing using the apparatus for aspirating, irrigating and/or cleansing wounds of the present invention.

The present invention will now be described by way of example only with reference to the accompanying drawings in which:

Figure 1 is a schematic view of an apparatus for aspirating, irrigating and/or cleansing a wound according to the first aspect of the present invention.

It has a single-phase system means for fluid cleansing in the form of an ultrafiltration unit.

The dressing in the apparatus is shown schematically with the means for applying stress to the wound bed omitted for clarity.

- 5 Figure 2 is a schematic view of an apparatus for aspirating, irrigating and/or cleansing a wound according to the first aspect of the present invention.

It has a two-phase system means for fluid cleansing in the form of a dialysis unit, or a biphasic extraction unit.

10

Figures 3 to 7 are cross-sectional views of conformable wound dressings, of the second aspect of the present invention for aspirating and/or irrigating wounds.

- 15 In these, Figures 3a to 5a are cross-sectional plan views of the wound dressings, and Figures 3b, 5b, 6 and 7 are cross-sectional side views of the wound dressings.

Referring to Figure 1, the apparatus (1) for aspirating, irrigating and/or  
20 cleansing wounds comprises

a conformable wound dressing (2), having

a backing layer (3) which is capable of forming a relatively fluid-tight seal or closure (4) over a wound (5) and

25 one inlet pipe (6) for connection to a fluid supply tube (7), which passes through the wound-facing face of the backing layer (5) at (8), and

one outlet pipe (9) for connection to a fluid offtake tube (10), which passes through the wound-facing face at (11),

the points (8), (11) at which the inlet pipe and the outlet pipe passes through and/or under the wound-facing face forming a relatively fluid-tight seal or

30 closure over the wound, and

means for stressing the wound in the form of a fluid-inflatable filler (111) (omitted for clarity) adapted to be inflated with air supplied through an

inflation inlet pipe (150), mounted centrally and in passing through the backing layer (3) above the filler (111) from a small, portable diaphragm

35 pump (151) with a bleed valve (116) by which air may be released from the filler (111),

the inlet pipe is connected via means for flow switching between supply and recirculation, here a T- valve (14), by the fluid supply tube (7) to a fluid reservoir (12) and to a fluid recirculation tube (13) having a means for bleeding the tube, here a bleed T-valve (16) to waste, e.g. to a collection bag (not shown),

the outlet pipe (9) being connected to a fluid offtake tube (15), connected in turn to

means for fluid cleansing (17), here in the form of an ultrafiltration unit, connected to the inlet pipe (6) via the fluid recirculation tube (13) and T- valve (14), and

a device for moving fluid through the wound and means for fluid cleansing (17), here a peristaltic pump (18), e.g. preferably a small portable peristaltic pump, acting on the fluid circulation tube (13) with the peripheral rollers on its rotor (not shown) to apply a low negative pressure on the wound.

The ultrafiltration unit (17) is a single-phase system.

In this the circulating fluid from the wound and the fluid reservoir passes through a self-contained system in which materials deleterious to wound healing are removed and the cleansed fluid, still containing materials that are beneficial in promoting wound healing, is returned via the recirculation tube to the wound bed.

(In a variant of this apparatus, there are two inlet pipes (6), which are connected respectively to a fluid supply tube (7) and fluid recirculation tube (13), respectively having a first valve (19) for admitting fluid into the wound from the fluid reservoir (12) and a second valve (20) for admitting fluid into the wound from the recirculation tube.

Usually in use of the apparatus, when the first valve (19) is open, the second valve (20) is shut, and vice versa.)

In use of the apparatus, if the inflation system bleed valve (116) by which air may be released from the filler (111) is open, it is then closed. The pump (151) is started to inflate the filler (111) with air through the inflation inlet pipe (150) towards the desired pressure on the wound bed.



The running of the pump (150) is continued until desired pressure is reached, and meanwhile the valve (16) is opened to a collection bag (not shown), and the T- valve (14) is turned to admit fluid from the fluid reservoir to the wound dressing through the fluid supply tube (7) and inlet pipe (6).

5

(In the variant of this apparatus having two inlet pipes (6), which are connected respectively to a fluid supply tube (7) and fluid recirculation tube (13), the first valve (19) for admitting fluid into the wound from the fluid reservoir (12) is opened and the second valve (20) is shut, and vice versa.)

10

The pump (18) is started to nip the fluid recirculation tube (13) with the peripheral rollers on its rotor (not shown) to apply a low positive pressure on the wound. It is allowed to run until the apparatus is primed throughout the whole length of the apparatus flow path and excess fluid is voided to waste via the bleed T-valve (16) into the collection bag (not shown).

15

The T-valve (14) is then turned to switch from supply and recirculation, i.e. is set to close the wound to the fluid reservoir (12) but to admit fluid into the wound from the fluid recirculation tube (13), and the bleed T-valve (16) is simultaneously closed.

20

(In the variant of this apparatus, where there are two inlet pipes (6), which are connected respectively to a fluid supply tube (7) and fluid recirculation tube (13), the first valve (19) is closed and a recirculating system set up by opening the second valve (20) for admitting fluid into the wound from the recirculation tube (13).

25

The circulating fluid from the wound and the fluid reservoir (12) passes through the ultrafiltration unit (17). Materials deleterious to wound healing are removed and the cleansed fluid, till containing materials that are beneficial in promoting wound healing, is returned via the recirculation tube (13) to the wound bed.

30

The recirculation of fluid may be continued as long as desired.

35

At any time after steady state recirculation has been achieved, the pressure on the wound bed and/or the fluid thereover may be varied, preferably cyclically, either randomly or regularly. This can be done by stopping the pump (151) and opening the closed inflation system bleed valve (116) so that  
 5 air is released from the filler (111) to deflate it to a second desired pressure on the wound bed.

The inflation – deflation cycle may be continue as long as desired.

10 To stop the apparatus (1) switching between supply and recirculation is reversed, by turning the T- valve (14) to admit fluid from the fluid reservoir to the wound dressing through the fluid supply tube (7) and inlet pipe (6).

(In the variant of this apparatus having two inlet pipes (6), which are  
 15 connected respectively to a fluid supply tube (7) and fluid recirculation tube (13), the first valve (19) for admitting fluid into the wound from the fluid reservoir (12) is opened and the second valve (20) is shut, and vice versa.)  
 The bleed valve (16) is simultaneously opened, so that fresh fluid flushes the recirculating system.

20 The running of the pump (18) may be continued until the apparatus is flushed, when it and the fluid recirculation is stopped.

If, e.g. the wound is in a highly exuding state, there is a positive change in  
 25 the balance of fluid in recirculation. It may be necessary to bleed fluid from recirculation, by opening the bleed T-valve (16) to bleed fluid from the recirculation tube (13).

Referring to Figure 2, the apparatus (21) is a variant of that of Figure 1, with  
 30 identical, and identically numbered, components, except for the means for fluid cleansing, which is in the form of a two-phase system, here a dialysis unit (23).

In this, there is one system through which the circulating fluid from the wound  
 35 and the fluid reservoir passes and from which deleterious materials are

removed by selectively permeable contact with a second system, through which passes a cleansing fluid.

The dialysis unit (23) thus has an internal polymer film, sheet or membrane (24), selectively permeable to materials deleterious to wound healing, which divides it into

a) a first chamber (25), through which passes a cleansing fluid across one surface of the polymer film, sheet or membrane, and

b) a second chamber (26), through which passes the circulating fluid from the wound and the fluid reservoir (12), and from which deleterious materials are removed

The dialysis unit (23) thus has a dialysate inlet pipe (28) connecting to a dialysate supply tube (29) which passes to a peristaltic pump (38), e.g. preferably a small portable peristaltic pump, acting on the dialysate supply tube (29) with the peripheral rollers on its rotor (not shown).

This supplies cleansing fluid across the surface of the polymer film, sheet or membrane (24) in the first chamber (25) from a dialysate reservoir (not shown) via a valve (34).

The dialysis unit (23) also has a dialysate outlet pipe (30) connecting to a dialysate outlet tube (31) which passes to waste via a second bleed T-valve (36) into, e.g. a collection bag (not shown).

Operation of this apparatus is similar to that of Figure 1, except for the dialysis unit (23):

At some point after the irrigation system is primed and steady state recirculation established through the length of the apparatus flow path, the valve (34) and second bleed valve (36) are opened.

The pump (38) is started to nip fluid dialysate tube (29) with the peripheral rollers on its rotor (not shown) to pump cleansing fluid to the first chamber from a dialysate reservoir (not shown) and out to waste via the bleed valve (36) into the collection bag (not shown).

The dialysis unit (23) is a module (or scrubbing cartridge) with a substrate that changes colour to indicate the presence of detrimental factors in the cleansed fluid, and that the scrubbing cartridge is exhausted and should be renewed.

Referring to Figures 3 to 7, each dressing (41) is in the form of a conformable body defined by a microbe-impermeable film backing layer (42) with a uniform thickness of 25 micron, with a wound-facing face (43) which is capable of forming a relatively fluid-tight seal or closure over a wound.

The backing layer (42) extends in use on a wound over the skin around the wound. On the proximal face of the backing layer (43) on the overlap (44), it bears an adhesive film (45), to attach it to the skin sufficiently to hold the wound dressing in place in a fluid-tight seal around the periphery of the wound-facing face (43) of the wound dressing.

There is one inlet pipe (46) for connection to a fluid supply tube (not shown), which passes through and/or under the wound-facing face (43), and one outlet pipe (47) for connection to a fluid offtake tube (not shown), which passes through and/or under the wound-facing face (43),

Referring to Figures 3a and 3b, a more suitable form for shallower wounds is shown. This comprises a circular backing layer (42) and a circular upwardly dished first membrane (61) with apertures (62) that is permanently attached to the backing layer (42) by heat-sealing to form a circular pouch (63).

The pouch (63) communicates with the inlet pipe (46) through a hole (64), and thus effectively forms an inlet pipe manifold that delivers the circulating fluid directly to the wound when the dressing is in use.

An annular second membrane (65) with openings (66) is permanently attached to the backing layer (42) by heat-sealing to form an annular chamber (67) with the layer (42).

The chamber (67) communicates with the outlet pipe (47) through an orifice (68), and thus effectively forms an outlet pipe manifold that collects the fluid directly from the wound when the dressing is in use.

- 5 Referring to Figures 4a and 4b, a variant of the dressing of Figures 3a and 3b that is a more suitable form for deeper wounds is shown.

10 This comprises a circular backing layer (42) and a filler (69), in the form of an inverted frustoconical, solid integer, here a resilient elastomeric foam, formed of a thermoplastic, or preferably a cross-linked plastics foam.

It is permanently attached to the backing layer (43), with an adhesive film (not shown) or by heat-sealing.

- 15 A circular upwardly dished sheet (70) lies under and conforms to, but is a separate structure, permanently unattached to, the backing layer (42) and the solid integer (69).

20 A circular upwardly dished first membrane (71) with apertures (72) is permanently attached to the sheet (70) by heat-sealing to form a circular pouch (73) with the sheet (70).

25 The pouch (73) communicates with the inlet pipe (46) through a hole (74), and thus effectively forms an inlet pipe manifold that delivers the circulating fluid directly to the wound when the dressing is in use.

30 An annular second membrane (75) with openings (76) is permanently attached to the sheet (70) by heat-sealing to form an annular chamber (77) with the sheet (70).

The chamber (77) communicates with the outlet pipe (77) through an orifice (78), and thus effectively forms an outlet pipe manifold that collects the fluid directly from the wound when the dressing is in use.

- 35 Alternatively, where appropriate the dressing may be provided in a form in

which the circular upwardly dished sheet (70) functions as the backing layer and the solid filler (69) sits on the sheet (70) as the backing layer, rather than under it. The filler (69) is held in place with an adhesive film or tape, instead of the backing layer (42).

5

Referring to Figures 5a and 5b, a dressing that is a more suitable form for deeper wounds is shown.

This comprises a circular backing layer (42) and a filler (79), in the form of an inverted generally hemispherical integer, here a resilient elastomeric foam or a hollow body filled with a fluid, here a gel that urges it to the wound shape, and permanently attached to the backing layer with an adhesive film (not shown) or by heat-sealing.

10 The inlet pipe (46) and outlet pipe (47) are mounted peripherally in the backing layer (42).

A circular upwardly dished sheet (80) lies under and conforms to, but is a separate structure, permanently unattached to, the backing layer (42) and the filler (79).

A circular upwardly dished bilaminate membrane (81) has a closed channel (82) between its laminar components, with perforations (83) along its length on the outer surface (84) of the dish formed by the membrane (81) and an opening (85) at the outer end of its spiral helix, through which the channel (82) communicates with the inlet pipe (46), and thus effectively forms an inlet pipe manifold that delivers the circulating fluid directly to the wound when the dressing is in use.

25

30 The membrane (81) also has apertures (86) between and along the length of the turns of the channel (82).

The inner surface (87) of the dish formed by the membrane (81) is permanently attached at its innermost points (88) with an adhesive film (not

35

shown) or by heat-sealing to the sheet (80). This defines a mating closed spirohelical conduit (89).

5 At the outermost end of its spiral helix, the conduit (89) communicates through an opening (90) with the outlet pipe (47) and is thus effectively an outlet manifold to collect the fluid directly from the wound via the apertures (86).

10 Referring to Figures 6 and 7, these forms of the dressing are provided with a wound filler (348) under a circular backing layer (342).

This comprises respectively a generally downwardly domed or oblately spheroidal conformable hollow body, defined by a membrane (349) which is filled with a fluid, here air or nitrogen, that urges it to the wound shape.

15 The filler (348) is permanently attached to the backing layer via a boss (351), which is e.g. heat-sealed to the backing layer (342).

20 An inflation inlet pipe (350), inlet pipe (346) and outlet pipe (347) are mounted centrally in the boss (351) in the backing layer (342) above the hollow body (348). The inflation inlet pipe (350) communicates with the interior of the hollow body (348), to permit inflation of the body (348).

25 The inlet pipe (346) extends in a pipe (352) effectively through the hollow body (348). The outlet pipe (347) extends radially immediately under the backing layer (342).

30 In Figure 6, the pipe (352) communicates with an inlet manifold (353), formed by a membrane (361) with apertures (362) that is permanently attached to the filler (348) by heat-sealing. It is filled with foam (363) formed of a suitable material, e.g. a resilient thermoplastic. Preferred materials include reticulated filtration polyurethane foams with small apertures or pores.


35 In Figure 7, the outlet pipe (347) communicates with a layer of foam (364) formed of a suitable material, e.g. a resilient thermoplastic. Again, preferred

materials include reticulated filtration polyurethane foams with small apertures or pores.

5 In both of Figures 6 and 7, in use, the pipe (353) ends in one or more openings that deliver the irrigant fluid directly from the wound bed over an extended area.


10 Similarly, the outlet pipe (347) effectively collects the fluid radially from the wound periphery when the dressing is in use.

This form of the dressing is a more suitable layout for deeper wounds.














**Figure 2**



70




Figure 3a




Figure 3b







Figure 4a



Section Through X -X

Figure 4b





72




Figure 5a




Figure 5b






Figure 6




Figure 7

